



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



BR-CAM Series Borescope Camera probes



Bright LED lights on camera probe tip to illuminate dark areas. Includes tip attachments (hook, mirror, and magnet).

Features

- For use with Extech Models BR100, BR200, and BR250 video borescopes
- Use different camera head sizes with the same video borescope depending on the space requirements
- 4.5mm and 5.5mm come with a 1m cable
- 9mm and 17mm cameras come with a 1m, 2m or 5m cable

Specifications	BR-4CAM	BR-5CAM	BR-9CAM (-XM)	BR-17CAM (-XM)
Resolution	712 x 486 pixels	720 x 525 pixels	712 x 486 pixels	640x480 pixels
Viewing Angle	63°	48°	45°	50°
Length	1m (3.3')	1m (3.3')	1m (3.3'), 2m (6.6'), or 5m (16.4')	1m (3.3'), 2m (6.6'), or 5m (16.4')
Outer diameter (O.D.)	4.5mm (0.178")	5.5mm (0.22")	9mm (0.35")	17mm (0.67")
Focus distance	2cm-7cm (0.8 to 2.8")	2cm-5cm (0.8 to 2")	8 to 15cm (3.2 to 5.9")	8 to 15cm (3.2 to 5.9")
Operating Temperature	-10 to 50°C (14 to 122°F)	-10 to 50°C (14 to 122°F)	-10 to 50°C (14 to 122°F)	-10 to 50°C (14 to 122°F)

Ordering

- BR-4CAM..... 4.5mm Borescope Camera Head (1m cable)
- BR-5CAM..... 5.5mm Borescope Camera Head (1m cable)
- BR-9CAM..... 9mm Borescope Camera Head (1m cable)
- BR-9CAM-2M 9mm Borescope Camera Head (2m cable)
- BR-9CAM-5M 9mm Borescope Camera Head (5m cable)
- BR-17CAM..... 17mm Borescope Camera Head (1m cable)
- BR-17CAM-2M 17mm Borescope Camera Head (2m cable)
- BR-17CAM-5M 17mm Borescope Camera Head (5m cable)