

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. NOTES: DIMENSIONS WIRE PANDU I T 1. UL LISTED AND CSA CERTIFIED FOR: COLOR in. A. 600 V MAX. VOLTAGE RATING PART NUMBER RANGE CODE B. TEMPERATURE RATING OF INSULATION: 150° (221° F) (AWG) MAX WIRE A ± 020 ID #\*050|OD ±.020 C. SOLID OR STRANDED, COPPER WIRE (,51) INSUL DIA (,51) (,51) 2. MATERIAL: .115 0.20 1.15 0.13 BSN18 RED \*\*\*22-18 A. STAMPING (22-18 & 16-14) - .03 [0.8] (2,92)(29,2)(3,3)(5,1)THK COPPER, TIN PLATED B. STAMPING (12-10) - .04 [1.0] 1.15 0.15 0.20 .148 BSN14 BLUE \*\*16-14 THK COPPER, TIN PLATED (29,2)(3,9)(5,1)(3,76)C. BRAZED SEAM D. HOUSING - NYLON .210 0.21 0.27 1.14 BSN10 \*12-10|YELLOW В (5.33)(29.0)(5,3)(6.8)3. ALL DIMENSIONS ARE IN INCHES EXCEPT DIMENSIONS IN BRACKETS WHICH ARE MILLIMETERS 4. INSTALLATION TOOLS: CT-100, CT-1550, CT-1551 \* 12-10 AWG STRANDED AND 12 AWG SOLID COPPER WIRE WITH CT-1550 & CT-1551 TOOLS 18-14 AWG WIRE RANGE LISTED CERTIFIED WITH CT-1550 AND CT-1551 TOOLS LR31212 587H \*\*\* 22-16 AWG WIRE RANGE WITH CT-1550 AND CT-1551 TOOLS E52164 6. WIRE STRIP LENGTH: BSN18 & BSN14 - 9/32 + 1/32 [7.1 + 0.8] - 0 - 0 BSN10 - 9/32 + 1/32 [7.1 + 0.8] – HOUS I NG 7. SEE www.PANDUIT.COM FOR PACKAGE QUANTITIES INDICATED BY PART NUMBER SUFFIX OD ID - SPL I CE WIRE STOPS (DESIGN MAY VARY) TITLE NYLON INSULATED BUTT SPLICES CUSTOMER DRAWING ITEM REVISION NAME N41182BA/13 DATASET FILE NAME N41182BA/13 MATERIAL: UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [ mm ] .X ± .XXX ± .XX ± ANGLES ± DRAWING NUMBER: ADDED NOTE ON BRAZED SEAM AND PACKAGING 13 2/15 TMR TMR RGB N41182BA-DC THIRD ANGLE A41182 REVISED TITLE BLOCK PROJECTION DRAWN BY DATE SCALE. REV DATE BY CHK APR ECN DESCRIPTION FES RLS SHT 1 0F 1 N/A 2

В

Α