



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

SIPMOS® Small-Signal-Transistor

Features


- N-Channel
- Enhancement mode
- Avalanche rated
- Logic Level
- dv/dt rated
- Pb-free lead plating; RoHS compliant
- Qualified according to AEC Q101



Product Summary

| | | | |
|----------------------------------|--------------|------|----------|
| Drain source voltage | V_{DS} | 60 | V |
| Drain-Source on-state resistance | $R_{DS(on)}$ | 0.09 | Ω |
| Continuous drain current | I_D | 2.6 | A |

| Pin 1 | Pin 2, 4 | PIN 3 |
|-------|----------|-------|
| G | D | S |



drain pins 2, 4



gate pin 1

source pin3

| Type | Package | Tape and Reel | Marking | Packaging |
|---------|-----------|-------------------|---------|-----------|
| BSP318S | PG-SOT223 | L6327: 1000 pcs/r | BSP318S | Non dry |

Maximum Ratings, at $T_j = 25^\circ\text{C}$, unless otherwise specified

| Parameter | Symbol | Value | Unit |
|--|----------------|-------------|-------------------|
| Continuous drain current $T_A = 25^\circ\text{C}$ | I_D | 2.6 | A |
| Pulsed drain current $I_D = 2.6 \text{ A}, V_{DD} = 25 \text{ V}, R_{GS} = 25 \Omega$ | I_D puls | 10.4 | |
| Avalanche energy, single pulse $I_D = 2.6 \text{ A}, V_{DD} = 25 \text{ V}, R_{GS} = 25 \Omega$ | E_{AS} | 60 | mJ |
| Avalanche current, periodic limited by T_{jmax} | I_{AR} | 2.6 | A |
| Avalanche energy, periodic limited by T_{jmax} | E_{AR} | 0.18 | mJ |
| Reverse diode dv/dt $I_S = 2.6 \text{ A}, V_{DS} = 20 \text{ V}, di/dt = 200 \text{ A}/\mu\text{s}, T_{jmax} = 150^\circ\text{C}$ | dv/dt | 6 | kV/ μs |
| Gate source voltage | V_{GS} | ± 20 | V |
| Power dissipation $T_A = 25^\circ\text{C}$ | P_{tot} | 1.8 | W |
| Operating and storage temperature | T_j, T_{stg} | -55... +150 | °C |
| IEC climatic category; DIN IEC 68-1 | | 55/150/56 | |
| ESD Class JESD22-A114-HBM | | Class 1b | |

Thermal Characteristics

| Parameter | Symbol | Values | | | Unit |
|---|------------|--------|------|------|------|
| | | min. | typ. | max. | |
| Characteristics | | | | | |
| Thermal resistance, junction - soldering point (Pin 4) | R_{thJS} | - | 17 | - | K/W |
| SMD version, device on PCB: @ min. footprint @ 6 cm ² cooling area ¹⁾ | R_{thJA} | - | 100 | - | |
| | | - | - | 70 | |

Electrical Characteristics, at $T_j = 25^\circ\text{C}$, unless otherwise specified

| Parameter | Symbol | Values | | | Unit |
|--|---------------------|--------|------|------|---------------|
| | | min. | typ. | max. | |
| Static Characteristics | | | | | |
| Drain- source breakdown voltage $V_{GS} = 0 \text{ V}$, $I_D = 0.25 \text{ mA}$ | $V_{(BR)DSS}$ | 60 | - | - | V |
| Gate threshold voltage, $V_{GS} = V_{DS}$ $I_D = 20 \mu\text{A}$ | $V_{GS(\text{th})}$ | 1.2 | 1.6 | 2 | |
| Zero gate voltage drain current $V_{DS} = 60 \text{ V}$, $V_{GS} = 0 \text{ V}$, $T_j = 25^\circ\text{C}$ $V_{DS} = 60 \text{ V}$, $V_{GS} = 0 \text{ V}$, $T_j = 150^\circ\text{C}$ | I_{DSS} | - | 0.1 | 1 | μA |
| - | | - | - | 100 | |
| Gate-source leakage current $V_{GS} = 20 \text{ V}$, $V_{DS} = 0 \text{ V}$ | I_{GSS} | - | 10 | 100 | nA |
| Drain-Source on-state resistance $V_{GS} = 4.5 \text{ V}$, $I_D = 2.6 \text{ A}$ | $R_{DS(\text{on})}$ | - | 0.12 | 0.15 | Ω |
| Drain-Source on-state resistance $V_{GS} = 10 \text{ V}$, $I_D = 2.6 \text{ A}$ | $R_{DS(\text{on})}$ | - | 0.07 | 0.09 | |

¹Device on 50mm*50mm*1.5mm epoxy PCB FR4 with 6cm² (one layer, 70 μm thick) copper area for drain connection. PCB is vertical without blown air.

Electrical Characteristics, at $T_j = 25^\circ\text{C}$, unless otherwise specified

| Parameter | Symbol | Values | | | Unit |
|--|--------------|--------|------|------|------|
| | | min. | typ. | max. | |
| Dynamic Characteristics | | | | | |
| Transconductance $V_{DS} \geq 2^* I_D * R_{DS(on)max}$, $I_D = 2.6 \text{ A}$ | g_{fs} | 2.4 | 5.5 | - | S |
| Input capacitance $V_{GS} = 0 \text{ V}$, $V_{DS} = 25 \text{ V}$, $f = 1 \text{ MHz}$ | C_{iss} | - | 300 | 380 | pF |
| Output capacitance $V_{GS} = 0 \text{ V}$, $V_{DS} = 25 \text{ V}$, $f = 1 \text{ MHz}$ | C_{oss} | - | 90 | 120 | |
| Reverse transfer capacitance $V_{GS} = 0 \text{ V}$, $V_{DS} = 25 \text{ V}$, $f = 1 \text{ MHz}$ | C_{rss} | - | 50 | 65 | |
| Turn-on delay time $V_{DD} = 30 \text{ V}$, $V_{GS} = 4.5 \text{ V}$, $I_D = 2.6 \text{ A}$, $R_G = 16 \Omega$ | $t_{d(on)}$ | - | 12 | 20 | ns |
| Rise time $V_{DD} = 30 \text{ V}$, $V_{GS} = 4.5 \text{ V}$, $I_D = 2.6 \text{ A}$, $R_G = 16 \Omega$ | t_r | - | 15 | 25 | |
| Turn-off delay time $V_{DD} = 30 \text{ V}$, $V_{GS} = 4.5 \text{ V}$, $I_D = 2.6 \text{ A}$, $R_G = 16 \Omega$ | $t_{d(off)}$ | - | 20 | 30 | |
| Fall time $V_{DD} = 30 \text{ V}$, $V_{GS} = 4.5 \text{ V}$, $I_D = 2.6 \text{ A}$, $R_G = 16 \Omega$ | t_f | - | 15 | 25 | |

Electrical Characteristics, at $T_j = 25^\circ\text{C}$, unless otherwise specified

| Parameter | Symbol | Values | | | Unit |
|------------------|---------------|---------------|-------------|-------------|-------------|
| | | min. | typ. | max. | |

Dynamic Characteristics

| | | | | | |
|---|------------------------|---|-----|-----|----|
| Gate charge at threshold $V_{DD} = 40 \text{ V}, I_D = 0.1 \text{ A}, V = 1 \text{ V}$ | $Q_{G(\text{th})}$ | - | 0.4 | 0.6 | nC |
| Gate charge at $V_{GS} = 5 \text{ V}$ $V_{DD} = 40 \text{ V}, I_D = 2.6 \text{ A}, V_{GS} = 0 \text{ to } 5 \text{ V}$ | $Q_g(5)$ | - | 7 | 10 | |
| Gate charge total $V_{DD} = 40 \text{ V}, I_D = 2.6 \text{ A}, V_{GS} = 0 \text{ to } 10 \text{ V}$ | Q_g | - | 14 | 20 | |
| Gate plateau voltage $V_{DD} = 40 \text{ V}, I_D = 2.6 \text{ A}$ | $V_{(\text{plateau})}$ | - | 3.6 | - | V |


| Parameter | Symbol | Values | | | Unit |
|------------------|---------------|---------------|-------------|-------------|-------------|
| | | min. | typ. | max. | |

Reverse Diode

| | | | | | |
|---|----------|---|------|------|---------------|
| Inverse diode continuous forward current $T_A = 25^\circ\text{C}$ | I_S | - | - | 2.6 | A |
| Inverse diode direct current,pulsed $T_A = 25^\circ\text{C}$ | I_{SM} | - | - | 10.4 | |
| Inverse diode forward voltage $V_{GS} = 0 \text{ V}, I_F = 5.2 \text{ A}$ | V_{SD} | - | 0.95 | 1.2 | V |
| Reverse recovery time $V_R = 30 \text{ V}, I_F = I_S, di_F/dt = 100 \text{ A}/\mu\text{s}$ | t_{rr} | - | 50 | 75 | ns |
| Reverse recovery charge $V_R = 30 \text{ V}, I_F = I_S, di_F/dt = 100 \text{ A}/\mu\text{s}$ | Q_{rr} | - | 0.1 | 0.15 | μC |


Power Dissipation

$$P_{\text{tot}} = f(T_A)$$



Drain current


$$I_D = f(T_A)$$



Safe operating area

$$I_D = f(V_{DS})$$


parameter : $D = 0$, $T_A = 25^\circ\text{C}$



Transient thermal impedance

$$Z_{\text{thJA}} = f(t_p)$$


parameter : $D = t_p/T$



Typ. output characteristic

$I_D = f(V_{DS})$; $T_j = 25^\circ\text{C}$


parameter: $t_p = 80 \mu\text{s}$



Typ. transfer characteristics $I_D = f(V_{GS})$

$V_{DS} \geq 2 \times I_D \times R_{DS(\text{on})\text{max}}$


parameter: $t_p = 80 \mu\text{s}$



Drain-source on-resistance

$R_{DS(\text{on})} = f(T_j)$


parameter: $I_D = 2.6 \text{ A}$, $V_{GS} = 4.5 \text{ V}$



Gate threshold voltage


$V_{GS(\text{th})} = f(T_j)$

parameter: $V_{GS} = V_{DS}$, $I_D = 20 \mu\text{A}$




Typ. capacitances

$$C = f(V_{DS})$$


 parameter: $V_{GS}=0$ V, $f=1$ MHz

Forward characteristics of reverse diode

$$I_F = f(V_{SD})$$


 parameter: T_j , $t_p = 80 \mu\text{s}$

Avalanche Energy $E_{AS} = f(T_j)$

 parameter: $I_D = 2.6$ A, $V_{DD} = 25$ V

$$R_{GS} = 25 \Omega$$



Typ. gate charge

$$V_{GS} = f(Q_{Gate})$$

 parameter: $I_D = 2.6$ A pulsed


Drain-source breakdown voltage

$$V_{(BR)DSS} = f(T_j)$$



Published by
Infineon Technologies AG
81726 Munich, Germany
© 2008 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office. Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.