



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





**Product
Improvement
Notice**

10/15/15

BU-32603-*
(Shrouded Banana Plug)



Old (4 Leaf) Banana

New (9 Leaf) Banana

The BU-32603 has been redesigned to utilize a 9 leaf banana plug. The old 4 leaf banana plug did not always mate with every manufacturers banana jacks. The issue is that the cantilever design of the 4 leaf plug does not have sufficient collapsible range to fit smaller ID banana jacks. Mueller has decided to use a nine leaf design that accommodates all known standard 4mm banana jacks. This new banana will assemble and function the same or better than the previous version.

BU-32603-*
(Shrouded Banana Plug)

(Revised 10/15/15)



Assembly photo (Wire not included)

The BU-32603 is a IEC 1010 compliant Banana plug.

- Fits 4mm Banana jacks that accept shrouded banana plugs.
- Easy solder connection with wire between 14-18 AWG
- Material: Housing – Nylon
Contact – Nickel plated Brass and Beryllium Copper
- Colors: designated by “*” in the part number: -0 black, -2 red, -4 Yellow, -6 Blue, -9 White
- Ratings: 20 Amps, 1000V Cat III, 1500V Cat II
- RoHS Compliant