

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









BU-7042-F-XX-*

(Dual Tip Probe Test Lead)



DESCRIPTION:

The BU-7042-F-xx-*is a dual pogo tipped test probe. Each probe tip is spring loaded to promote solid contact when the probe is held at an angle or the surface being tested is uneven. The tab at the end of the probe corresponds to the tab on the dual 4mm banana plug. The connecting cable is RG174 and has a 50 Ohm impedance. The pin spacing on the probe is .124"

Available Lengths: "XX" in the part number indicates length in inches; 44, 48, 144 Available colors: "*" in part number indicates color; -0=Black; -2=Red {shown}

MATERIAL: Contact: Gold plated beryllium Copper

Body: Polypropylene

Ratings: 30 Volts Max.

RoHS Compliant

Mueller Electric Company 1208 Massillon Rd. Ste. N-1500 Akron, OH 44306-4524

www.muellerelectric.com

Toll Free: 800.955.2629 Phone: 330.780.2525 Fax: 330.780.2524