

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









## **BU-P2249-C-XX**

(Test Lead, BNC with Strain Relief on Each End, RG-58C/U)



Materials:

■ Cable: Cable is RG 58C/U, complies to Mil-M17/155-00001

Jacket is non-contaminating PVC

Center conductor is 20 AWG (19x33) tinned copper

Shield is tinned copper braid (95% coverage)

■ Male BNC: Body is tarnish resistant nickel plated brass

Center Contact is Gold plated brass

Insulator is PTFE

■ Strain Relief is Molded PVC that is bonded to the BNC.

• Ratings: Impedance: 50 Ohms

Capacitance per foot: 30.8 pf

Power Loss/100 Ft. @ 1 MHz: .40 dB Hands free testing to 500 VRMS

Operating Temperature: -40°C to 85°C

• Ordering: The "XX" in the part number represents the length in Inches.

Standard lengths: 6", 12", 24", 36", 48", 60", 72", 120", 144" 180", 240", 300", and 600"

RoHS Compliant, CE Compliant

Toll Free: 800.955.2629

Phone: 330.780.2525

Fax: 330.780.2524