



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




# RAM controller for CD player

## BU9348K

● Description

The BU9348K is an IC incorporating function that can protect pop noise electrically by using DRAM together for CD players. This IC is available for four types of DRAM. Four shockproof mode(4bit, 5bit, 6bit, non-compression) and through mode can be selected.

● Dimension (Unit : mm)



**QFP44**

● Features

- 1) Available for 4 types of DRAM (16MDRAM, 4MDRAMx2, 4MDRAM, 1MDRAM)
- 2) Four shockproof mode(4bit, 5bit, 6bit, non-compression) and through mode selectable
- 3) Available for x4 speed(Max.)
- 4) Built-in digital attenuator and soft mute function
- 5) Built-in extended I/O function

● Applications

Portable CD players

● Absolute Maximum Ratings (Ta=25°C)

Parameter	Symbol	Limits	Unit
Supply voltage	Vcc	-0.3 ~ 4.5	V
Power dissipation	Pd	500 *	mW
Operating temperature range	Topr	-25 ~ +75	°C
Storage temperature range	Tstg	-55 ~ +125	°C

\*Derating : 5mW/°C for operation above Ta=25°C

● Recommended Operating Conditions (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit
Supply voltage	Vcc	2.7	3.0	3.6	V

● Electrical characteristics (Unless otherwise noted; Ta=25°C, Vcc=3.0V)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Current consumption (Shock proof mode)	IDD	-	8.9	20	mA	Shock proof mode
Current consumption (Through mode)	IDD	-	1.8	5.0	mA	Through mode

● Block diagram

