



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

Logic level TOPFET

SMD version of BUK104-50L/S

BUK114-50L/S

DESCRIPTION

Monolithic temperature and overload protected logic level power MOSFET in a 5 pin surface mounting plastic envelope, intended as a general purpose switch for automotive systems and other applications.

APPLICATIONS

General controller for driving
 • lamps
 • motors
 • solenoids
 • heaters

FEATURES

- Vertical power DMOS output stage
- Low on-state resistance
- Logic and protection supply from separate pin
- Low operating supply current
- Overload protection against over temperature
- Overload protection against short circuit load
- Latched overload protection reset by protection supply
- Protection circuit condition indicated by flag pin
- 5 V logic compatible input level
- Separate input pin for higher frequency drive
- ESD protection on input, flag and protection supply pins
- Over voltage clamping for turn off of inductive loads
- Both linear and switching operation are possible

QUICK REFERENCE DATA

| SYMBOL | PARAMETER | MAX. | UNIT |
|--------------|----------------------------------|------|------------------|
| V_{DS} | Continuous drain source voltage | 50 | V |
| I_D | Continuous drain current | 15 | A |
| P_{tot} | Total power dissipation | 40 | W |
| T_J | Continuous junction temperature | 150 | °C |
| $R_{DS(ON)}$ | Drain-source on-state resistance | | |
| | $V_{IS} = 5 \text{ V}$ | 125 | $\text{m}\Omega$ |
| | $V_{IS} = 7 \text{ V}$ | 100 | $\text{m}\Omega$ |
| SYMBOL | PARAMETER | NOM. | UNIT |
| V_{PSN} | Protection supply voltage | | |
| | BUK114-50L | 5 | V |
| | BUK114-50S | 10 | V |


FUNCTIONAL BLOCK DIAGRAM

Fig.1. Elements of the TOPFET.

PINNING - SOT426

| PIN | DESCRIPTION |
|-----|-------------------|
| 1 | input |
| 2 | flag |
| 3 | (connected to mb) |
| 4 | protection supply |
| 5 | source |
| mb | drain |


PIN CONFIGURATION

Fig. 2.


SYMBOL

Fig. 3.

Logic level TOPFET

SMD version of BUK104-50L/S

BUK114-50L/S

LIMITING VALUES

Limiting values in accordance with the Absolute Maximum Rating System (IEC 134)

| SYMBOL | PARAMETER | CONDITIONS | MIN. | MAX. | UNIT |
|--|---|--|--------------------------------------|------|--------------------|
| V_{DSS} V_{IS} V_{FS} V_{PS} I_D I_{DPM} P_{tot} T_{stg} T_j T_{sold} | Voltages Continuous off-state drain source voltage ¹ | $V_{IS} = 0 \text{ V}$ | - | 50 | V |
| | Continuous input voltage | - | 0 | 11 | V |
| | Continuous flag voltage | - | 0 | 11 | V |
| | Continuous supply voltage | - | 0 | 11 | V |
| | Currents | $V_{IS} =$ $T_{mb} \leq 25 \text{ }^\circ\text{C}$ $T_{mb} \leq 100 \text{ }^\circ\text{C}$ $T_{mb} \leq 25 \text{ }^\circ\text{C}$ | - | 7 | V |
| | Continuous drain current | | - | 15 | A |
| | Continuous drain current | | - | 9.5 | A |
| | Repetitive peak on-state drain current | | - | 60 | A |
| | - | | - | 13 | |
| | - | | - | 8.5 | |
| | - | | - | 54 | |
| | Thermal | | $T_{mb} = 25 \text{ }^\circ\text{C}$ | - | W |
| | Total power dissipation | | - | 40 | |
| | Storage temperature | | -55 | 150 | ${}^\circ\text{C}$ |
| | Junction temperature ² | | - | 150 | ${}^\circ\text{C}$ |
| | Lead temperature | | - | 250 | ${}^\circ\text{C}$ |

OVERLOAD PROTECTION LIMITING VALUES

With the protection supply connected, TOPFET can protect itself from two types of overload - over temperature and short circuit load.

An n-MOS transistor turns on between the input and source to quickly discharge the power MOSFET gate capacitance.

For internal overload protection to remain latched while the control circuit is high, external series input resistance must be provided. Refer to INPUT CHARACTERISTICS.

| SYMBOL | PARAMETER | CONDITIONS | MIN. | MAX. | UNIT |
|--------------|--|--|------|------|------|
| V_{PSP} | Protection supply voltage ³ | $V_{IS} =$ for valid protection BUK114-50L BUK114-50S | 7 | 5 | - |
| | | | 4.4 | 4 | V |
| | | | 5.4 | 5 | V |
| $V_{DDP(T)}$ | Over temperature protection Protected drain source supply voltage | $V_{PS} = V_{PSN}$ $V_{IS} = 10 \text{ V}; R_I \geq 2 \text{ k}\Omega$ $V_{IS} = 5 \text{ V}; R_I \geq 1 \text{ k}\Omega$ | - | 50 | V |
| $V_{DDP(P)}$ | Short circuit load protection Protected drain source supply voltage ⁴ | $V_{PS} = V_{PSN}; L \leq 10 \mu\text{H}$ $V_{IS} = 10 \text{ V}; R_I \geq 2 \text{ k}\Omega$ $V_{IS} = 5 \text{ V}; R_I \geq 1 \text{ k}\Omega$ | - | 25 | V |
| P_{DSM} | Instantaneous overload dissipation | - | 45 | 0.8 | kW |

ESD LIMITING VALUE

| SYMBOL | PARAMETER | CONDITIONS | MIN. | MAX. | UNIT |
|--------|---|--|------|------|------|
| V_C | Electrostatic discharge capacitor voltage | Human body model; $C = 250 \text{ pF}; R = 1.5 \text{ k}\Omega$ | - | 2 | kV |

¹ Prior to the onset of overvoltage clamping. For voltages above this value, safe operation is limited by the overvoltage clamping energy.

² A higher T_j is allowed as an overload condition but at the threshold $T_{j(TO)}$ the over temperature trip operates to protect the switch.

³ The minimum supply voltage required for correct operation of the overload protection circuits.

⁴ The device is able to self-protect against a short circuit load providing the drain-source supply voltage does not exceed $V_{DDP(P)}$ maximum. For further information, refer to OVERLOAD PROTECTION CHARACTERISTICS.

Logic level TOPFET
SMD version of BUK104-50L/S

BUK114-50L/S

OVERVOLTAGE CLAMPING LIMITING VALUES

At a drain source voltage above 50 V the power MOSFET is actively turned on to clamp overvoltage transients.

| SYMBOL | PARAMETER | CONDITIONS | MIN. | MAX. | UNIT |
|---------------|---|--|------|------|------|
| $I_{D_{RRM}}$ | Repetitive peak clamping drain current | $R_{IS} \geq 100 \Omega^1$ | - | 15 | A |
| E_{DSM} | Non-repetitive inductive turn-off energy ² | $I_{DM} = 15 \text{ A}; R_{IS} \geq 100 \Omega$ | - | 200 | mJ |
| E_{DRM} | Repetitive inductive turn-off energy | $R_{IS} \geq 100 \Omega; T_{mb} \leq 95^\circ\text{C}; I_{DM} = 4 \text{ A}; V_{DD} \leq 20 \text{ V}; f = 250 \text{ Hz}$ | - | 20 | mJ |
| I_{DIRM} | Repetitive peak drain to input current ³ | $R_{IS} = 0 \Omega; t_p \leq 1 \text{ ms}$ | - | 50 | mA |

REVERSE DIODE LIMITING VALUE

| SYMBOL | PARAMETER | CONDITIONS | MIN. | MAX. | UNIT |
|--------|----------------------------|---|------|------|------|
| I_s | Continuous forward current | $T_{mb} = 25^\circ\text{C}; V_{IS} = V_{PS} = V_{FS} = 0 \text{ V}$ | - | 15 | A |

THERMAL CHARACTERISTIC

| SYMBOL | PARAMETER | CONDITIONS | MIN. | TYP. | MAX. | UNIT |
|---------------|---|------------|------|------|------|------|
| $R_{th,j-mb}$ | Thermal resistance Junction to mounting base | - | - | 2.5 | 3.1 | K/W |

STATIC CHARACTERISTICS $T_{mb} = 25^\circ\text{C}$ unless otherwise specified

| SYMBOL | PARAMETER | CONDITIONS | MIN. | TYP. | MAX. | UNIT |
|---------------|----------------------------------|---|------|------|------|------------------|
| $V_{(CL)DSR}$ | Drain-source clamping voltage | $R_{IS} = 100 \Omega; I_D = 10 \text{ mA}$ | 50 | - | 65 | V |
| $V_{(CL)DSR}$ | Drain-source clamping voltage | $R_{IS} = 100 \Omega; I_{DM} = 1 \text{ A}; t_p \leq 300 \mu\text{s}; \delta \leq 0.01$ | 50 | - | 70 | V |
| I_{DSS} | Zero input voltage drain current | $V_{DS} = 12 \text{ V}; V_{IS} = 0 \text{ V}$ | - | 0.5 | 10 | μA |
| I_{DSR} | Drain source leakage current | $V_{DS} = 50 \text{ V}; R_{IS} = 100 \Omega;$ | - | 1 | 20 | μA |
| I_{DSR} | Drain source leakage current | $V_{DS} = 40 \text{ V}; R_{IS} = 100 \Omega; T_j = 125^\circ\text{C}$ | - | 10 | 100 | μA |
| $R_{DS(ON)}$ | Drain-source on-state resistance | $I_{DM} = 7.5 \text{ A}; V_{IS} = 7 \text{ V}$ | - | 75 | 100 | $\text{m}\Omega$ |
| | | $t_p \leq 300 \mu\text{s}; \delta \leq 0.01$ | - | 95 | 125 | $\text{m}\Omega$ |

¹ The input pin must be connected to the source pin by a specified external resistance to allow the power MOSFET gate source voltage to become sufficiently positive for active clamping. Refer to INPUT CHARACTERISTICS.

² While the protection supply voltage is connected, during overvoltage clamping it is possible that the overload protection may operate at energies close to the limiting value. Refer to OVERLOAD PROTECTION CHARACTERISTICS.

³ Shorting the input to source with low resistance inhibits the internal overvoltage protection by preventing the power MOSFET gate source voltage becoming positive.

Logic level TOPFET

SMD version of BUK104-50L/S

BUK114-50L/S

OVERLOAD PROTECTION CHARACTERISTICS

With adequate protection supply voltage TOPFET detects when one of the overload thresholds is exceeded.

Provided there is adequate input series resistance it switches off and remains latched off until reset by the protection supply pin.

Refer also to OVERLOAD PROTECTION LIMITING VALUES and INPUT CHARACTERISTICS.

| SYMBOL | PARAMETER | CONDITIONS | MIN. | TYP. | MAX. | UNIT |
|-----------------------------|--|--|------|------------|------|---------------|
| $E_{DS(TO)}$ $t_{d\ sc}$ | Short circuit load protection¹ Overload threshold energy Response time | $V_{PS} = V_{PSN}^2$; $T_{mb} = 25^\circ C$; $L \leq 10 \mu H$; $R_I \geq 2 k\Omega$ $V_{DD} = 13 V$; $V_{IS} = 10 V$ $V_{DD} = 13 V$; $V_{IS} = 10 V$ | - | 150 375 | - | mJ μs |
| $T_{I(TO)}$ | Over temperature protection Threshold junction temperature | $V_{PS} = V_{PSN}$; $R_I \geq 2 k\Omega$ from $I_D \geq 0.65 A^3$ | 150 | - | - | °C |

TRANSFER CHARACTERISTICS

$T_{mb} = 25^\circ C$

| SYMBOL | PARAMETER | CONDITIONS | MIN. | TYP. | MAX. | UNIT |
|----------|----------------------------|---|------|----------|------|------|
| g_{fs} | Forward transconductance | $V_{DS} = 10 V$; $I_{DM} = 7.5 A$ $t_p \leq 300 \mu s$; $\delta \leq 0.01$ | 5 | 9 | - | S |
| I_D | Drain current ⁴ | $V_{DS} = 13 V$; $V_{IS} = 5 V$ $V_{IS} = 10 V$ | - | 25 40 | - | A |

PROTECTION SUPPLY CHARACTERISTICS

$T_{mb} = 25^\circ C$ unless otherwise specified

| SYMBOL | PARAMETER | CONDITIONS | MIN. | TYP. | MAX. | UNIT |
|-------------------------|---|--|------|------|------|------|
| I_{PS} , I_{PSL} | Protection supply Protection supply current | normal operation or protection latched BUK114-50L $V_{PS} = 5 V$ BUK114-50S $V_{PS} = 10 V$ | - | 0.2 | 0.35 | mA |
| V_{PSR} | Protection reset voltage ⁵ | $T_j = 150^\circ C$ | 1.5 | 2.5 | 3.5 | V |
| $V_{(CL)PS}$ | Protection clamp voltage | $I_P = 1.35 mA$ | 1.0 | - | - | V |
| | | | 11 | 13 | - | V |

REVERSE DIODE CHARACTERISTICS

$T_{mb} = 25^\circ C$

| SYMBOL | PARAMETER | CONDITIONS | MIN. | TYP. | MAX. | UNIT |
|-----------|-----------------------|--|------|------|------|------|
| V_{SDS} | Forward voltage | $I_S = 15 A$; $V_{IS} = V_{PS} = V_{FS} = 0 V$; $t_p = 300 \mu s$ | - | 1.0 | 1.5 | V |
| t_{rr} | Reverse recovery time | not applicable ⁶ | - | - | - | - |

¹ The short circuit load protection is able to save the device providing the instantaneous on-state dissipation is less than the limiting value for P_{DSM} , which is always the case when V_{DS} is less than V_{DSP} maximum.

² At the appropriate nominal protection supply voltage for each type. Refer to QUICK REFERENCE DATA.

³ The over temperature protection feature requires a minimum on-state drain source voltage for correct operation. The specified minimum I_D ensures this condition.

⁴ During overload condition. Refer also to OVERLOAD PROTECTION LIMITING VALUES and CHARACTERISTICS.

⁵ The supply voltage below which the overload protection circuits will be reset.

⁶ The reverse diode of this type is not intended for applications requiring fast reverse recovery.

Logic level TOPFET
SMD version of BUK104-50L/S

BUK114-50L/S

INPUT CHARACTERISTICS $T_{mb} = 25^\circ\text{C}$ unless otherwise specified

| SYMBOL | PARAMETER | CONDITIONS | MIN. | TYP. | MAX. | UNIT |
|--------------|---|---|------------------|----------------------|------------------|--|
| $V_{IS(TO)}$ | Normal operation Input threshold voltage | $V_{DS} = 5 \text{ V}; I_D = 1 \text{ mA}$ $T_{mb} = 150^\circ\text{C}$ | 1.0 0.5 | 1.5 - | 2.0 - | V V |
| I_{IS} | Input current | $V_{IS} = 10 \text{ V}$ | - | 10 | 100 | nA |
| $V_{(CL)IS}$ | Input clamp voltage | $I_I = 1 \text{ mA}$ | 11 | 13 | - | V |
| R_{ISL} | Overload protection latched Input resistance ¹ | $V_{PS} = 5 \text{ V}$ $I_I = 5 \text{ mA};$ $T_{mb} = 150^\circ\text{C}$ $V_{PS} = 10 \text{ V}$ $I_I = 5 \text{ mA};$ $T_{mb} = 150^\circ\text{C}$ | - - - - | 55 95 35 60 | - - - - | Ω Ω Ω Ω |
| R_{IS} | Application information External input resistances for internal overvoltage clamping ² | (see figure 29) | | | | |
| R_I | internal overload protection ³ | $R_I = \infty \Omega; V_{DS} > 30 \text{ V}$ $R_{IS} = \infty \Omega; V_{II} = 5 \text{ V}$ $V_{II} = 10 \text{ V}$ | 100 1 2 | - - - | - - - | Ω $k\Omega$ $k\Omega$ |

SWITCHING CHARACTERISTICS $T_{mb} = 25^\circ\text{C}; R_I = 50 \Omega; R_{IS} = 50 \Omega$ (see figure 29); resistive load $R_L = 10 \Omega$. For waveforms see figure 28.

| SYMBOL | PARAMETER | CONDITIONS | MIN. | TYP. | MAX. | UNIT |
|--------------|---------------------|---|------|------|------|------|
| $t_{d(on)}$ | Turn-on delay time | $V_{DD} = 15 \text{ V}; V_{IS}: 0 \text{ V} \Rightarrow 10 \text{ V}$ | - | 8 | - | ns |
| t_r | Rise time | | - | 13 | - | ns |
| $t_{d(off)}$ | Turn-off delay time | $V_{DD} = 15 \text{ V}; V_{IS}: 10 \text{ V} \Rightarrow 0 \text{ V}$ | - | 100 | - | ns |
| t_f | Fall time | | - | 45 | - | ns |

CAPACITANCES $T_{mb} = 25^\circ\text{C}; f = 1 \text{ MHz}$

| SYMBOL | PARAMETER | CONDITIONS | MIN. | TYP. | MAX. | UNIT |
|-----------|-----------------------------------|---|------|------|------|------|
| C_{iss} | Input capacitance | $V_{DS} = 25 \text{ V}; V_{IS} = 0 \text{ V}$ | - | 415 | 600 | pF |
| C_{oss} | Output capacitance | $V_{DS} = 25 \text{ V}; V_{IS} = 0 \text{ V}$ | - | 275 | 400 | pF |
| C_{rss} | Reverse transfer capacitance | $V_{DS} = 25 \text{ V}; V_{IS} = 0 \text{ V}$ | - | 55 | 80 | pF |
| C_{ps0} | Protection supply pin capacitance | $V_{PS} = 10 \text{ V}$ | - | 30 | - | pF |
| C_{fso} | Flag pin capacitance | $V_{FS} = 10 \text{ V}; V_{PS} = 0 \text{ V}$ | - | 20 | - | pF |

1 The resistance of the internal transistor which discharges the power MOSFET gate capacitance when overload protection operates.

The external drive circuit should be such that the input voltage does not exceed $V_{IS(TO)}$ minimum when the overload protection has operated. Refer also to figure for latched input characteristics.2 Applications using a lower value for R_{IS} would require external overvoltage protection.3 For applications requiring a lower value for R_I , an external overload protection strategy is possible using the flag pin to 'tell' the control circuit to switch off the input.

Logic level TOPFET
SMD version of BUK104-50L/S

BUK114-50L/S

FLAG DESCRIPTION

The flag pin provides a means to detect the presence of the protection supply and indicate the state of the overload detectors. The flag is the open drain of an n-MOS transistor and requires an external pull-up resistor¹. It is suitable for both 5 V and 10 V logic. Flag may be used to implement an external protection strategy² for applications which require low input drive impedance.

TRUTH TABLE

| CONDITION | DESCRIPTION | FLAG |
|---------------|---|------------|
| NORMAL | Normal operation and adequate protection supply voltage | LOGIC LOW |
| OVER TEMP. | Over temperature detected | LOGIC HIGH |
| SHORT CIRCUIT | Overload condition detected | LOGIC HIGH |
| SUPPLY FAULT | Inadequate protection supply voltage | LOGIC HIGH |

FLAG CHARACTERISTICS $T_{mb} = 25^\circ\text{C}$ unless otherwise stated

| SYMBOL | PARAMETER | CONDITIONS | MIN. | TYP. | MAX. | UNIT |
|-----------------------|---|---|----------------------|----------------------|--------------------|--------------------------------------|
| V_{FS} I_{FSS} | Flag 'low' Flag voltage Flag saturation current | normal operation $I_F = 1.6 \text{ mA}$ $V_{FS} = 10 \text{ V}$ | - - | 0.15 15 | 0.4 - | V mA |
| I_{FS} V_{PSF} | Flag 'high' Flag leakage current Protection supply threshold voltage | overload or fault $V_{FS} = 10 \text{ V}$ $V_{FF} = 5 \text{ V}; R_F = 3 \text{k}\Omega;$ BUK114-50L BUK114-50S | - - 2.5 3.3 | - - 3.3 4.2 | 10 10 4 5 | μA V V |
| $V_{(CL)FS}$ | Flag clamping voltage | $I_F = 1 \text{ mA}; V_{PS} = 0 \text{ V}$ | 11 | 13 | - | V |
| R_F | Application information Suitable external pull-up resistance | $V_{FF} = 5 \text{ V}$ $V_{FF} = 10 \text{ V}$ | 1 2 | 10 20 | 50 100 | $\text{k}\Omega$ $\text{k}\Omega$ |

1 Even if the flag pin is not used, it is recommended that it is connected to the protection supply via a pull-up resistor. It should not be left floating.

2 Low pass filtering of the flag signal may be advisable to prevent false tripping.

Logic level TOPFET

SMD version of BUK104-50L/S

BUK114-50L/S




Fig.4. Normalised limiting power dissipation.
 $P_D\% = 100 \cdot P_D/P_D(25\text{ }^\circ\text{C}) = f(T_{mb})$




Fig.7. Transient thermal impedance.
 $Z_{th,j-mb} = f(t)$; parameter $D = t_p/T$




Fig.5. Normalised continuous drain current.
 $I_D\% = 100 \cdot I_D/I_D(25\text{ }^\circ\text{C}) = f(T_{mb})$; conditions: $V_{IS} = 5\text{ V}$




Fig.8. Typical output characteristics, $T_j = 25\text{ }^\circ\text{C}$.
 $ID = f(V_{DS})$; parameter $V_{IS}/V =$




Fig.6. Safe operating area. $T_{mb} = 25\text{ }^\circ\text{C}$
 $I_D \& I_{DM} = f(V_{DS})$; I_{DM} single pulse; parameter t_p




Fig.9. Typical on-state characteristics, $T_j = 25\text{ }^\circ\text{C}$.
 $I_D = f(V_{DS})$; parameter V_{IS} ; $t_p = 250\text{ }\mu\text{s}$

Logic level TOPFET

SMD version of BUK104-50L/S

BUK114-50L/S




Fig.10. Typical on-state resistance, $T_j = 25^\circ\text{C}$.
 $R_{DS(ON)} = f(I_D)$; parameter V_{IS} ; $t_p = 250\ \mu\text{s}$




Fig.13. Normalised drain-source on-state resistance.
 $a = R_{DS(ON)}/R_{DS(ON)25^\circ\text{C}} = f(T_j)$; $I_D = 7.5\text{ A}$; $V_{IS} \geq 5\text{ V}$




Fig.11. Typical transfer characteristics, $T_j = 25^\circ\text{C}$.
 $I_D = f(V_{IS})$; conditions: $V_{DS} = 10\text{ V}$; $t_p = 250\ \mu\text{s}$




Fig.14. Typical over temperature protection threshold
 $T_{j(TO)} = f(V_{PS})$; conditions: $V_{DS} > 0.1\text{ V}$




Fig.12. Typical transconductance, $T_j = 25^\circ\text{C}$.
 $g_{fs} = f(I_D)$; conditions: $V_{DS} = 10\text{ V}$; $t_p = 250\ \mu\text{s}$




Fig.15. Normalised limiting overload dissipation.
 $P_{DSM}\% = 100 \cdot P_{DSM}/P_{DSM}(25^\circ\text{C}) = f(T_{mb})$

Logic level TOPFET

SMD version of BUK104-50L/S

BUK114-50L/S




Fig. 16. Maximum drain source supply voltage for SC load protection. $V_{DDP(P)} = f(V_{IS})$; $T_{mb} \leq 150^\circ\text{C}$




Fig. 19. Typical overload protection characteristics. Conditions: $V_{DD} = 13\text{ V}$; $V_{PS} = V_{PSN}$, $V_{IS} = 7\text{ V}$; SC load




Fig. 17. Minimum protection supply voltage for SC load protection. $V_{PSP} = f(V_{IS})$; $T_{mb} \geq 25^\circ\text{C}$




Fig. 20. Typical overload protection energy, $T_j = 25^\circ\text{C}$. $E_{SC(TO)} = f(V_{PS})$; conditions: $V_{DS} = 13\text{ V}$, parameter V_{IS}




Fig. 18. Typical overload protection characteristics. $t_{dsc} = f(P_{DS})$; conditions: $V_{PS} \geq V_{PSP}$; $V_{IS} \geq 5\text{ V}$




Fig. 21. Typical clamping characteristics, 25°C . $I_D = f(V_{DS})$; conditions: $R_{IS} = 100\Omega$; $t_p \leq 50\mu\text{s}$

Logic level TOPFET

SMD version of BUK104-50L/S

BUK114-50L/S




Fig.22. Input threshold voltage.
 $V_{IS(TO)} = f(T_j)$; conditions: $I_D = 1 \text{ mA}$; $V_{DS} = 5 \text{ V}$




Fig.25. Typical reverse diode current, $T_j = 25^\circ\text{C}$.
 $I_S = f(V_{SD})$; conditions: $V_{IS} = 0 \text{ V}$; $t_p = 250 \mu\text{s}$




Fig.23. Typical DC protection supply characteristics.
 $I_{PS} = f(V_{PS})$; normal or overload operation; $T_j = 25^\circ\text{C}$




Fig.26. Normalised limiting clamping energy.
 $E_{DSM}\% = f(T_{mb})$; conditions: $I_D = 15 \text{ A}$




Fig.24. Typical latched input characteristics, 25°C .
 $I_{ISL} = f(V_{IS})$; after overload protection latched




Fig.27. Clamping energy test circuit, $R_{IS} = 100 \Omega$.
 $E_{DSM} = 0.5 \cdot L I_D^2 \cdot V_{(CL)DSR} / (V_{(CL)DSR} - V_{DD})$

Logic level TOPFET

SMD version of BUK104-50L/S

BUK114-50L/S




Fig.28. Typical resistive load switching waveforms.
 $R_I = R_{IS} = 50 \Omega$; $R_L = 10 \Omega$; $V_{DD} = 15 V$; $T_j = 25^\circ C$




Fig.31. Typical off-state leakage current.
 $I_{DSR} = f(T_j)$; Conditions: $V_{DS} = 40 V$; $R_{IS} = 100 \Omega$.




Fig.29. External input resistances R_I and R_{IS} , generator voltage V_{II} and input voltage V_{IS} .




Fig.32. Normalised protection supply current.
 $I_{PS}/I_{PS}25^\circ C = f(T_j)$; $V_{PS} = V_{PSN}$




Fig.30. Typical capacitances, C_{iss} , C_{oss} , C_{rss} .
 $C = f(V_{DS})$; conditions: $V_{IS} = 0 V$; $f = 1 MHz$

**Logic level TOPFET
SMD version of BUK104-50L/S****BUK114-50L/S****MECHANICAL DATA***Dimensions in mm*

Net Mass: 1.5 g




Fig.33. SOT426

mounting base connected to centre pin (cropped short)


MOUNTING INSTRUCTIONS*Dimensions in mm*

Fig.34. SOT426

soldering pattern for surface mounting.

**Logic level TOPFET
SMD version of BUK104-50L/S****BUK114-50L/S****DEFINITIONS**

| Data sheet status | |
|--|---|
| Objective specification | This data sheet contains target or goal specifications for product development. |
| Preliminary specification | This data sheet contains preliminary data; supplementary data may be published later. |
| Product specification | This data sheet contains final product specifications. |
| Limiting values | |
| Limiting values are given in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of this specification is not implied. Exposure to limiting values for extended periods may affect device reliability. | |
| Application information | |
| Where application information is given, it is advisory and does not form part of the specification. | |
| © Philips Electronics N.V. 1996 | |
| All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. | |
| The information presented in this document does not form part of any quotation or contract, it is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights. | |

LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.