

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China











| NO. | | PIN NUMBER | MATING WIRE HARNESS | | |
|-----|---|-------------------------|---------------------|--|--|
| | 1 | INPUT (+12V) | | | |
| CN1 | 2 | GND | | | |
| | 3 | CNT (L = ON) | BXC-10549 | | |
| | 4 | VR1 (GND) | | | |
| | 5 | VR1 POTENTIOMETER (10K) | | | |
| | 1 | OUTPUT (HV) | | | |
| CN2 | 2 | NO CONNECTION | BXC-10643 | | |
| | 3 | OUTPUT (LV) | | | |

NOTE:

MATING CONNECTORS ARE NOT INCLUDED WITH INVERTER. JKL WIRE HARNESS BXC-10549 AND BXC-10643 CAN BE ORDERED SEPARATELY.

*JKL PART NO.: BXA-12665-5M

*RoHS COMPLIANCE

OPERATING SPECIFICATIONS

| CHARACTERISTICS | MIN | TYP | MAX |
|---------------------------|------|------|------|
| INPUT VOLTAGE: (vdc) | 10.8 | 12.0 | 13.2 |
| INPUT CURRENT: (mA) | 200 | 230 | 260 |
| OUTPUT VOLTAGE: (Vrms) | | 1200 | |
| OUTPUT CURRENT: (mArms) | 4.5 | 5.0 | 5.5 |
| OUTPUT FREQUENCY: (kHz) | 55 | 65 | 75 |
| DIMMING RANGE (OPTION) | 40 | | 100 |
| OPERATING TEMP: (CELSIUS) | 0 | 25 | 50 |

| METRIC | DIMENSIONS ARE IN MILLIMETERS | | KI | COMPONI | ENTS CORPO | OD A T | ION |
|---|---|-------|----------|-------------|---------------|--------------|-------------------|
| 1 (0) + | TOLERANCE UNLESS | U. | | COMPONE | ENTS CORP | JKA I | ION |
| THIRD ANGLE PROJECTION | OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- ANGLE +/- 0 | TITLE | DIMI | MING INVERT | ER | | |
| DRAWN BY | APPV'D BY DATE | SIZE | FSCM NO. | DRAWING DV | (A 4000E EN | 4 | |
| L. WENGSTROM | L.R. 10/13/06 | A | 55335 | NO. BX | (A-12665-5N | I | |
| - CAD DRAWING - MANUAL REVISIONS NOT PERMITTED | | SCALE | | RELEASED | REVISION | REV. | SHEET |
| | | | NONE | 3/22/06 | DATE 10/13/06 | NO. A | 1 _{OF} 1 |