



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Damper-Modulator fast, high-voltage

BYM357X**FEATURES**

- Low forward volt drop
- Fast switching
- Soft recovery characteristic
- High thermal cycling performance
- Isolated mounting tab

SYMBOL**QUICK REFERENCE DATA**

DAMPER	MODULATOR
$V_R = 1500 \text{ V}$	$V_R = 600 \text{ V}$
$V_F \leq 1.3 \text{ V}$	$V_F \leq 1.03 \text{ V}$
$I_{F(\text{peak})} = 7 \text{ A}$	$I_{F(\text{peak})} = 7 \text{ A}$
$I_{FSM} \leq 60 \text{ A}$	$I_{FSM} \leq 70 \text{ A}$
$t_{rr} \leq 300 \text{ ns}$	$t_{rr} \leq 60 \text{ ns}$


GENERAL DESCRIPTION

Combined damper and modulator diodes in an isolated plastic envelope for horizontal deflection in colour TV and PC monitors. The BYM357X contains diodes with performance characteristics designed specifically for applications from 16kHz to 70kHz.

The BYM357X series is supplied in the conventional leaded SOT186A package.

PINNING

PIN	DESCRIPTION
1	damper cathode
2	common anode/cathode
3	modulator anode.

SOT186A**LIMITING VALUES**

$T_j = 25 \text{ }^\circ\text{C}$ unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS	DAMPER		MODULATOR		UNIT
			MIN	MAX	MIN	MAX	
V_{RSM}	Peak non-repetitive reverse voltage.		-	1500	-	600	V
V_{RRM}	Peak repetitive reverse voltage		-	1500	-	600	V
V_{RWM}	Crest working reverse voltage		-	1300	-	600	V
$I_{F(\text{peak})}$	Peak forward current	31-70 kHz monitor.	-	7	-	7	A
$I_{F(\text{RMS})}$	RMS forward current	sinusoidal; $a=1.57$	-	15.7	-	14.1	A
I_{FSM}	Peak non-repetitive forward current	$t = 10 \text{ ms}$	-	60	-	70	A
		$t = 8.3 \text{ ms}$ sinusoidal; with reappplied $V_{RWM(\text{MAX})}$	-	66	-	77	A
T_{stg}	Storage temperature		-40	150	-40	150	$^\circ\text{C}$
T_j	Operating junction temperature		-	150	-	150	$^\circ\text{C}$

Damper-Modulator fast, high-voltage

BYM357X

ISOLATION LIMITING VALUE & CHARACTERISTIC

 $T_{hs} = 25\text{ }^{\circ}\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V_{isol}	R.M.S. isolation voltage from all three terminals to external heatsink	$f = 50\text{-}60\text{ Hz}$; sinusoidal waveform; $R.H. \leq 65\%$; clean and dustfree	-	-	2500	V
C_{isol}	Capacitance from T2 to external heatsink	$f = 1\text{ MHz}$	-	10	-	pF

THERMAL RESISTANCES

SYMBOL	PARAMETER	CONDITIONS	DAMPER		MODULATOR		UNIT
			TYP.	MAX.	TYP.	MAX.	
$R_{th\ j\text{-}hs}$	Thermal resistance junction to heatsink	with heatsink compound	-	4.8	-	5.5	K/W
$R_{th\ j\text{-}a}$	Thermal resistance junction to ambient	in free air.	55	-	55	-	K/W

STATIC CHARACTERISTICS OF DAMPER

 $T_j = 25\text{ }^{\circ}\text{C}$ unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS	TYP	MAX.	UNIT
V_F	Forward voltage	$I_F = 6.5\text{ A}$	1.1	1.45	V
I_R	Reverse current	$I_F = 6.5\text{ A}; T_j = 125\text{ }^{\circ}\text{C}$	1.05	1.3	V
		$V_R = V_{RWM}$	10	250	μA
		$V_R = V_{RWM}$ $T_j = 100\text{ }^{\circ}\text{C}$	50	500	μA

STATIC CHARACTERISTICS OF MODULATOR

 $T_j = 25\text{ }^{\circ}\text{C}$ unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS	TYP	MAX.	UNIT
V_F	Forward voltage	$I_F = 8\text{ A}$	1.05	1.25	V
I_R	Reverse current.	$I_F = 8\text{ A}; T_j = 125\text{ }^{\circ}\text{C}$	0.9	1.03	V
		$I_F = 20\text{ A}$	1.3	1.45	V
		$V_R = V_{RWM}$	10	50	μA
		$V_R = V_{RWM}$	100	350	μA
		$T_j = 100\text{ }^{\circ}\text{C}$			

Damper-Modulator fast, high-voltage

BYM357X

ELECTRICAL CHARACTERISTICS OF DAMPER

$T_j = 25\text{ }^{\circ}\text{C}$ unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS	TYP.	MAX.	UNIT
t_{rr}	Reverse recovery time	$I_F = 1\text{ A}$; $V_R \geq 30\text{ V}$; $-dI_F/dt = 50\text{ A}/\mu\text{s}$	200	300	ns
Q_s	Reverse recovery charge	2 A , 30 V , $20\text{ A}/\mu\text{s}$	1.2	2.0	μC
V_{fr}	Peak forward recovery voltage	$I_F = 6.5\text{ A}$; $dI_F/dt = 50\text{ A}/\mu\text{s}$	27	-	V







ELECTRICAL CHARACTERISTICS OF MODULATOR

$T_j = 25\text{ }^{\circ}\text{C}$ unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS	TYP.	MAX.	UNIT
t_{rr}	Reverse recovery time	$I_F = 1\text{ A}$; $V_R \geq 30\text{ V}$; $-dI_F/dt = 100\text{ A}/\mu\text{s}$	35	60	ns
I_{rrm}	Peak reverse recovery current	$I_F = 10\text{ A}$ to $V_R \geq 30\text{ V}$; $dI_F/dt = 50\text{ A}/\mu\text{s}$; $T_j = 100^{\circ}\text{C}$	3.0	5.5	A
Q_s	Reverse recovery charge	2 A , 30 V , $20\text{ A}/\mu\text{s}$	40	70	nC
V_{fr}	Peak forward recovery voltage	$I_F = 10\text{ A}$; $dI_F/dt = 10\text{ A}/\mu\text{s}$	3.2	-	V

Damper-Modulator fast, high-voltage

BYM357X



Damper-Modulator fast, high-voltage

BYM357X




Fig.7. Modulator transient thermal impedance
 $Z_{th} = f(t_p)$




Fig.10. Damper transient thermal impedance
 $Z_{th} = f(t_p)$




Fig.8. Modulator typical and maximum forward characteristic; $I_F = f(V_F)$; parameter T_j




Fig.11. Damper forward characteristic $I_F = f(V_F)$; parameter T_j




Fig.9. Modulator maximum t_{rr} measured to 25% of I_{rrm} ; $T_j = 25^\circ\text{C}$ and 150°C

Damper-Modulator fast, high-voltage

BYM357X

MECHANICAL DATA

Dimensions in mm

Net Mass: 2 g




Fig.12. SOT186A; The seating plane is electrically isolated from all terminals.

Notes

1. Refer to mounting instructions for F-pack envelopes.
2. Epoxy meets UL94 V0 at 1/8".

Damper-Modulator fast, high-voltage

BYM357X

DEFINITIONS

Data sheet status	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
Limiting values	
Limiting values are given in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of this specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
Application information	
Where application information is given, it is advisory and does not form part of the specification.	
© Philips Electronics N.V. 2000	
All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.	
The information presented in this document does not form part of any quotation or contract, it is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights.	

LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.