

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







1250 Rocker Switches

10A 250Vac











Key Features

- Standard rocker switch
- O Double pole in single pole body
- O Snap in or sub panel mount
- Integral terminal barrier
- O Push on or PCB terminals
- Panel cut out: 27.2 x 12.4 (snap in) 26.3 x 12.4 (sub panel mount)

Terminal	Function	Rocker	Body	Body Colour	Rocker Colour	
C	2a 2 1a 1 On when pressed over terminal 1	A Curved	N Panel cut-out Bezel Sub-panel Facia (3.0)	B Black	B Black	
9.0 6.3 x 0.8	1250 2a 2 1a 1 ON - OFF Double pole Poles are 9.0mm between centres.	Shown in N body	Panel thickness Dim X 0.75-1.24 26.1/26.2 1.25-1.99 26.3/26.4 2.00-3.00 26.7/26.8	W White	W White	
X 5.2 \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	181 On when pressed over terminal 1	Shown in P body	Panel cut out Panel cut out 27.2/ 27.3 12.4/ 12.5 Panel thickness		G Grey	
PCB 0.8sq (N body only)	1250SP 1a • 1 ON - OFF Single pole		0.75-3.00 Cut-outs must be punched in the direction of insertion			



Approvals and specifications

10(6)A 250Vac T100 6A 400Vac T100 1A 30Vdc

91/8

UL CSA 10A 250Vac UL CSA 16A 250Vac Resistive UL CSA 125Vac 1/2hp UL CSA 1A 30Vdc UL 100°C, file E45221, CSA file LR10990

3mm contact gap

Dimensions

1250AN



1250AN (C terminals shown) (X terminals shown)



Terminal spacing 10.2 between pole centres

1250AP (C terminals shown)



Terminal spacing 10.2 between pole centres

Legend	Legend Colour	Options
Blank	Blank	Finish Matt finish only. Colour Call sales for custom colours. A full range is available for large orders.
085	B Black	Legend printing Select from the examples or call sales for custom legend.
	W White	