



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




FLORENCE-1R-Z2T25

Double asymmetric beam


TECHNICAL SPECIFICATIONS:

Dimensions	19.5 x 286.0 mm
Height	6.4 mm
Fastening	glue
Colour	clear
Box size	480 x 280 x 300 mm
Box weight	5.9 kg
Quantity in Box	210 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:



Component	Type	Material	Colour
FLORENCE-1R-Z2T25	Lens	PMMA	clear





PHOTOMETRIC DATA (MEASURED):





LED CALGD0414-M8W1
FWHM Asymmetric
Efficiency 88 %
Peak intensity 0.460 cd/lm
Required components:





LED CALGD0814-M17W1
FWHM Asymmetric
Efficiency 88 %
Peak intensity 0.460 cd/lm
Required components:



LED L0-280024-xxx-C0800-L267
FWHM Asymmetric
Efficiency 87 %
Peak intensity 0.420 cd/lm
Required components:




LED XH-B/G
FWHM Asymmetric
Efficiency 87 %
Peak intensity 0.410 cd/lm
Required components:



PHOTOMETRIC DATA (MEASURED):



LUMILEDS

LED LUXEON 3014
FWHM Asymmetric
Efficiency 91 %
Peak intensity 0.610 cd/lm
Required components:





LUMILEDS

LED LUXEON 3020
FWHM Asymmetric
Efficiency 91 %
Peak intensity 0.610 cd/lm
Required components:





LUMILEDS

LED LUXEON 3030 2D (Round LES)
FWHM Asymmetric
Efficiency 87 %
Peak intensity 0.460 cd/lm
Required components:



LUMILEDS



LED LUXEON 3535L
FWHM Asymmetric
Efficiency 90 %
Peak intensity 0.470 cd/lm
Required components:




PHOTOMETRIC DATA (MEASURED):





LED MP-2016
 FWHM Asymmetric
 Efficiency 88 %
 Peak intensity 0.590 cd/lm
 Required components:





LED NF2x757D
 FWHM Asymmetric
 Efficiency 87 %
 Peak intensity 0.430 cd/lm
 Required components:



LED NF2x757G
 FWHM Asymmetric
 Efficiency 87 %
 Peak intensity 0.440 cd/lm
 Required components:





LED Duris S5 (2 chip)
 FWHM Asymmetric
 Efficiency 87 %
 Peak intensity 0.430 cd/lm
 Required components:



PHOTOMETRIC DATA (MEASURED):


PHILIPS

LED Fortimo LED Line 1ft 1100lm xx0 1R xV2/x
FWHM Asymmetric
Efficiency 92 %
Peak intensity 0.490 cd/lm
Required components:





PHILIPS

LED Fortimo LED Line 1ft 2000lm 8x0 1R HV1/HV2
FWHM Asymmetric
Efficiency 91 %
Peak intensity 0.490 cd/lm
Required components:
C14353_FLORENCE-1R-CLIP-A





SAMSUNG

LED LM28xB Series
FWHM Asymmetric
Efficiency 90 %
Peak intensity 0.480 cd/lm
Required components:



SAMSUNG



LED LM301A
FWHM Asymmetric
Efficiency 88 %
Peak intensity 0.520 cd/lm
Required components:



PHOTOMETRIC DATA (MEASURED):



SAMSUNG

LED LM302A
FWHM Asymmetric
Efficiency 88 %
Peak intensity 0.480 cd/lm
Required components:





SAMSUNG

LED LM561C
FWHM Asymmetric
Efficiency 90 %
Peak intensity 0.520 cd/lm
Required components:





SAMSUNG

LED LT-S282N
FWHM Asymmetric
Efficiency 90 %
Peak intensity 0.470 cd/lm
Required components:




SEOUL SEMICONDUCTOR

LED SEOUL 3030
FWHM Asymmetric
Efficiency 88 %
Peak intensity 0.460 cd/lm
Required components:




PHOTOMETRIC DATA (MEASURED):



PHOTOMETRIC DATA (SIMULATED):


LG Innotek

LED LG 5630
 FWHM Asymmetric
 Efficiency 86 %
 Peak intensity cd/lm
 Required components:




LUMILEDS

LED LUXEON 2835 Line
 FWHM Asymmetric
 Efficiency 91 %
 Peak intensity 0.580 cd/lm
 Required components:




OSRAM Opto Semiconductors

LED Duris E 2835
 FWHM Asymmetric
 Efficiency 91 %
 Peak intensity 0.540 cd/lm
 Required components:



OSRAM Opto Semiconductors

LED Duris E5
 FWHM Asymmetric
 Efficiency 91 %
 Peak intensity 0.500 cd/lm
 Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)