



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



STRADELLA-16-HB-S

~25° spot beam for industrial applications


TECHNICAL SPECIFICATIONS:

Dimensions	49.5 mm
Height	7.5 mm
Fastening	pin, screw
Colour	clear
Box size	480 x 280 x 300 mm
Box weight	6.3 kg
Quantity in Box	800 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:


Component	Type	Material	Colour
STRADELLA-16-HB-S	Lens array	PMMA	clear



PHOTOMETRIC DATA (MEASURED):



LG Innotek

LED LG 3030
 FWHM 28.0°
 Efficiency 90 %
 Peak intensity 1.500 cd/lm
 Required components:





NICHIA

LED NFSx757D
 FWHM 25.0°
 Efficiency 90 %
 Peak intensity 1.700 cd/lm
 Required components:





NICHIA

LED NFSx757G
 FWHM 27.0°
 Efficiency 93 %
 Peak intensity 1.700 cd/lm
 Required components:



OSRAM


LED PrevaLED Brick DC 4x16
 FWHM 30.0°
 Efficiency 92 %
 Peak intensity 1.400 cd/lm
 Required components:



PHOTOMETRIC DATA (MEASURED):



OSRAM
Opto Semiconductors

LED Duris S5 (Single chip)
FWHM 23.0°
Efficiency 90 %
Peak intensity 2.000 cd/lm
Required components:





PHILIPS

LED Fortimo FastFlex LED 4x16 DHE G4
FWHM 29.0°
Efficiency 92 %
Peak intensity 1.500 cd/lm
Required components:



SAMSUNG



LED LM231 A/B
FWHM 22.0°
Efficiency 91 %
Peak intensity 2.000 cd/lm
Required components:








SEOUL

SEOUL SEMICONDUCTOR

LED SEOUL 3030
FWHM 26.0°
Efficiency 90 %
Peak intensity 1.700 cd/lm
Required components:




PHOTOMETRIC DATA (MEASURED):

<p> SEOUL SEMICONDUCTOR</p> <p>LED SunLike 3030 FWHM 24.0° Efficiency 94 % Peak intensity 1.900 cd/lm Required components:</p>		
<p>TRIDONIC</p> <p>LED RLE G2 MP 4x16 4000lm FWHM 29.0° Efficiency 93 % Peak intensity 1.500 cd/lm Required components:</p>		

PHOTOMETRIC DATA (SIMULATED):


LUMILEDS

LED LUXEON C
 FWHM 25.0°
 Efficiency 91 %
 Peak intensity 1.500 cd/lm
 Required components:




LUMILEDS

LED LUXEON C Colors
 FWHM 25.0°
 Efficiency 91 %
 Peak intensity 1.400 cd/lm
 Required components:




LUMILEDS

LED LUXEON C Colors
 FWHM 25.0°
 Efficiency 90 %
 Peak intensity 1.400 cd/lm
 Required components:



LUMILEDS


LED LUXEON CZ
 FWHM 22.0°
 Efficiency 94 %
 Peak intensity 2.400 cd/lm
 Required components:



PHOTOMETRIC DATA (SIMULATED):




LED NVSxE21A
FWHM 25.0°
Efficiency 92 %
Peak intensity 2.100 cd/lm
Required components:




SAMSUNG

LED LH351B
FWHM 33.0°
Efficiency 94 %
Peak intensity 1.627 cd/lm
Required components:




SAMSUNG

LED LH351C
FWHM 37.0°
Efficiency 94 %
Peak intensity 1.471 cd/lm
Required components:



SAMSUNG

LED LM301B
FWHM 27.0°
Efficiency 93 %
Peak intensity 1.870 cd/lm
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)