

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









## PRODUCT DATASHEET PART NUMBER: C6132NL

- Diplexer 5-1002/1125-1525 MHz
- Impedance = 75 Ohms
- Surface Mount
- RoHS-Compliant


	110110 001	прпан	Electrical S	Specifications @	25°C			
INSERTION LOSS: CATV								
5-1002 MHz	1125-1525 MHz	2300-3000 MHz	4600 MHz	6000 MHz				
1.5 dB Max	37 dB Min	35 dB Min	25 dB Min	5 dB Min				
INSERTION LOSS: MOCA								
5-42 MHz	42-1002 MHz	1125-1525 MHz	2300-3000 MHz	4600 MHz	6000 MHz			
60 dB Min	38 dB Min	2.5 dB Max	45 dB Min	25 dB Min	5 dB Min			
ISOLATION: (MOCA to CATV)								
5-42 MHz	42-1002 MHz	1125-1525 MHz	2300-3000 MHz	4600 MHz	6000 MHz			
60 dB Min	38 dB Min	37 dB Min	45 dB Min	25 dB Min	5 dB Min			
RETURN LOSS:								
5-1002 MHz	1125-1525 MHz							
14 dB Min	10 dB Min							
PASSBAND SLOPE:								
6 MHz BAND	50 MHz BAND							
5-1002 MHz	1125-1525 MHz							
0.35 dB Max	1.0 dB Max							

Pulse


043008-A



## **Mechanical Specifications**




DESIGNATIONS	
COMMON PORT (CP)	PIN 3
MOCA	PIN 7
CATV	PIN 15
GROUND (GND)	PINS 1,2,4,5
GROUND (GND)	PINS 6,8,14,16
GROUND (GND)	PINS 9-13





RIGHT SIDE VIEW



Dimensions: Inches

**Pulse** 

12220 World Trade Dr. San Diego, CA 92128 U.S.A. <u>www.pulseeng.com</u> TEL: 858 674 8100 FAX: 858 674 8262 043008-A