



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





GELWRAP WRAP-AROUND SPLICE COVER

EASILY INSTALL CONNECTIONS UP TO 1000V

KEY FEATURES

- Simply wrap and snap the sleeve on any cable in the use range
- Easy and quick to install
- For splice cover, cable rejacketing, underground or overhead applications
- Closure sleeves are compatible with solid dielectric cable insulations

TE Connectivity's (TE) Raychem GelWrap closure sleeves quickly and conveniently, insulate and seal buried electrical connections rated up to 1000 volts. The robust yet compact design is engineered to handle the harsh environments of direct burial and manhole applications. GelWrap sleeves are equally well suited for insulation and jacket repair.

PowerGel sealing material was specifically developed for the electrical power industry. This unique hydrophobic gel material provides an excellent moisture seal over wide operating temperature ranges (-40°C to 95°C). Both the gel and housing are UV resistant and suitable for overhead applications.


Other common uses for GelWrap sleeves include LV cable repair splices, MV cable jacket repair, MV splice rejacketing, and Elbow sealing sleeve.

Customers can count on consistent, high quality products, driven by TE's proven innovation and backed by our extraordinary customer support.

**TESTING**

The TE GelWrap sleeve meets the following requirements:

Testing	Test Conditions
ANSI C119.1 - 1986	600V insulated underground
Chemical Resistance	Fluid immersion, 168 hours @ 23° C, 75% elongation retention minimum <ul style="list-style-type: none"> - 10W-40 motor oil - 10% hydrochloric acid - 15% sodium chloride - 20% sodium hydroxide - ETX 60280 antifreeze (1000 hours)
Accelerated Aging	1000 hours @ 135° C <ul style="list-style-type: none"> - 93% retention tensile strength - 82% retention elongation at break

Maximum Mechanical Connector Dimensions:**Figure (A)****Figure (B)****PRODUCT SELECTION INFORMATION: DIMENSIONS IN INCHES (mm)**

Description	Sleeve Length	Conductor Size	Maximum Connector Opening	General Use Diameter Range
GelWrap-18/4-100	4.0 (100)	#12 - 4/0 (4 - 95)	1.0 (25)	0.15 - 0.70 (4 - 8)
GelWrap-18/4-150	6.0 (150)	#12 - 4/0 (4 - 95)	3.0 (75)	0.15 - 0.70 (4 - 18)
GelWrap-18/4-200	8.0 (200)	#12 - 4/0 (4 - 95)	5.0 (125)	0.15 - 0.70 (4 - 18)
GelWrap-18/4-250	10.0 (250)	#12 - 4/0 (4 - 95)	7.0 (175)	0.15 - 0.70 (4 - 18)
GelWrap-18/4-300	12.0 (300)	#12 - 4/0 (4 - 95)	9.0 (225)	0.15 - 0.70 (4 - 18)
GelWrap-33/10-150	6.0 (150)	#2 - 500 (35 - 240)	2.0 (50)	0.40 - 1.30 (10 - 33)
GelWrap-33/10-200	8.0 (200)	#2 - 500 (35 - 240)	4.0 (100)	0.40 - 1.30 (10 - 33)
GelWrap-33/10-250	10.0 (250)	#2 - 500 (35 - 240)	6.0 (150)	0.40 - 1.30 (10 - 33)
GelWrap-33/10-300	12.0 (300)	#2 - 500 (35 - 240)	8.0 (200)	0.40 - 1.30 (10 - 33)
GelWrap-33/10-350	14.0 (350)	#2 - 500 (35 - 240)	10.0 (250)	0.40 - 1.30 (10 - 33)
GelWrap-50/20-200	8.0 (200)	250 - 750	2.0 (50)	0.80 - 1.50 (20 - 38)
GelWrap-50/20-250	10.0 (250)	250 - 750	4.0 (100)	0.80 - 1.50 (20 - 38)
GelWrap-50/20-300	12.0 (300)	250 - 750	6.0 (150)	0.80 - 1.50 (20 - 38)
GelWrap-50/20-350	14.0 (350)	250 - 750	8.0 (200)	0.80 - 1.50 (20 - 38)
GelWrap-50/20-400	16.0 (400)	250 - 750	10.0 (250)	0.80 - 1.50 (20 - 38)

Note: For other sizes or application, a minimum seal length is required on each side of connector opening or jacket damage.

PRODUCT SELECTION INFORMATION: UL LISTED - DIMENSIONS IN INCHES (mm)

Description	Sleeve Length	1000V Cable Range	Maximum Connector Opening	Max. Compression Connector Diameter	Maximum Mechanical Connector Dimensions	
					Height (A)	Width (B)
GelWrap-18/4-150UL	6.0 (150)	#14-4/0 AWG	2.0 (50)	0.85 (22)	1.2 (30)	1.1 (28)
GelWrap-18/4-200UL	8.0 (200)	#14-4/0 AWG	4.0 (100)	0.85 (22)	1.2 (30)	1.1 (28)
GelWrap-18/4-250UL	10.0 (250)	#14-4/0 AWG	6.0 (150)	0.85 (22)	1.2 (30)	1.1 (28)
GelWrap-18/4-300UL	12.0 (300)	#14-4/0 AWG	8.0 (200)	0.85 (22)	1.2 (30)	1.1 (28)
GelWrap-18/4-350UL	14.0 (350)	#14-4/0 AWG	10.0 (250)	0.85 (22)	1.2 (30)	1.1 (28)
GelWrap-18/4-400UL	16.0 (400)	#14-4/0 AWG	12.0 (300)	0.85 (22)	1.2 (30)	1.1 (28)
GelWrap-18/4-450UL	18.0 (450)	#14-4/0 AWG	14.0 (350)	0.85 (22)	1.2 (30)	1.1 (28)
GelWrap-18/4-500UL	20.0 (500)	#14-4/0 AWG	16.0 (400)	0.85 (22)	1.2 (30)	1.1 (28)
GelWrap-18/4-550UL	22.0 (550)	#14-4/0 AWG	18.0 (450)	0.85 (22)	1.2 (30)	1.1 (28)
GelWrap-18/4-600UL	24.0 (600)	#14-4/0 AWG	20.0 (500)	0.85 (22)	1.2 (30)	1.1 (28)

FOR MORE INFORMATION: TE Technical Support Centers

te.com/energy

© 2005, 2007, 2009, 2012, 2014 TE Connectivity Ltd. family of companies. All Rights Reserved. 1309100 E157 10/2014

GelWrap, PowerGel, Raychem, TE Connectivity and TE connectivity (logo) are trademarks. Other logos, product and/or company names might be trademarks of their respective owners. While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

USA: +1 800 327 6996
 France: +33 380 583 200
 UK: +44 0870 870 7500
 Germany: +49 896 089 903
 Spain: +34 916 630 400
 Benelux: +32 16 351 731
 Canada: +1 (905) 475-6222
 Mexico: +52 (0) 55-1106-0800
 Latin/S. America: +54 (0) 11-4733-2200
 China: +86 (0) 400-820-6015