

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00381	Connector, dc plug, 5.5x2.1xL25 mm, molding style, spring contacts	1	
2	50-00025	Connector, dc jack, 5.5x2.1xL17.4 mm, molding style	1	
3	30-00007	Wire, 2C BC, 18 AWG, UL2468, 300V, 80C, 4.4 mm, VW-1, PVC, 87A	1	
4	24-00072	Overmold, PVC	1	black
5	24-00054	Overmold, PVC	1	black



Notes:

Hi-Pot test: 600 Vac, 0.5 mA, 1 second

Wiring Diagram								
50-00381	wire color	50-00025						
center	black with stripe	center						
sleeve	black	sleeve						

Revision:	Date:	Description:	Prepared:	epared: Notes:						
Α	1/19/2009	Re-issue CUI spec as Tensility	2016.09.07 12:14:13 -07'00'	RoHS and REACH compliant	TENSILITY					
A1	8/31/2011	Updated description, connector, and wire information	Verified: PS Digitally signed by PS Date: 2016.09.07 14:04:01 - 07'00'	Function test: no open, no short circuit, no intermittent			tel 1.541.323.3228 800 877.670.7118			
A2	9/10/2013	Updated connector	Dimensions are in	ensions are in		fax 1.541.323.4202 web tensility.com				
A3	2/14/2014	Updated connector	millimeters. Tolerances: X: ± 0.5 mm	lerances: + 0.5 mm Cable, 1830 mm, 5.5x2.1x12 mm, 90° 50-00381 plu				Part number: 053-0381R (CA-2213)		
			X.X: ± 0.3 mm X.XX: ± 0.05 mm	to 5.5x2.1 mm, 50-00025 jack, 18 AWG, 30-00007 wire		Scale:	1:1		Sheet 1 of 1	
		5	4	3	2				1	