



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us



Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	NOTES
1	50-00006	Connector, 2.5xL21.6 mm, audio plug 4C with metal ring, brass nickel plated	2	
2	30-00413	Wire, 4C TC, 26 AWG, 30V, 80C, 3.7 mm, shielded, PVC, 89A	1	
3	24-00104	Overmold, PVC, black	2	



Wiring Diagram		
50-00006	wire color	50-00006
A	Red	A
B	Black	B
C	Green	C
D	Yellow	D

Notes:

Electical requirement: 2 A

Hi-Pot test: 300 Vac, 0.5 mA, 1 second

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>
A	1/19/2009	Re-issued CUI spec as Tensility	GL 2016.02.22 10:44:42 -08'00'	RoHS and REACH compliant	
A1	5/11/2009	Added connector part number	LA <small>Digitally signed by LA DN: cn=LA, o=Tensility, ou=Engineering, email=LA002@Tensility.com, c=US Date: 2016.02.22 15:26:56 -08'00'</small>	Function test: no open, no short circuit, no intermittent	
A2	8/30/2011	Updated description and part number information	Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Cable, 1830 mm, 4C 2.5mm 50-00006 plug with metal ring to same, 26 AWG, 30-00413	
A3	5/6/2014	Updated description			Size: Part number: A 053-0110R (CA-254CS-MM)
					Scale: 1:1 Sheet 1 of 1