

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









# PRODUCT DATASHEET CA13752\_STRADA-SQ-FT

### STRADA-SQ-FT

Forward throw beam for area lighting. Assembly with installation tape. Version with location pins.

#### **TECHNICAL SPECIFICATIONS:**

Dimensions 25 + 25 mm

Height 12.7 mm

Fastening pin, screw, tape

Colour clear

Box size 480 x 280 x 300 mm

Box weight 7.2 kg

Quantity in Box 1568 pcs

ROHS compliant yes 1




#### **MATERIAL SPECIFICATIONS:**

Component	Туре	Material	Colour
STRADA-SQ-FT	Lens	PMMA	clear
ROSE-TAPE	Tape	PU tape	black



# PRODUCT DATASHEET CA13752\_STRADA-SQ-FT



# PRODUCT DATASHEET CA13752\_STRADA-SQ-FT

## PHOTOMETRIC DATA (MEASURED):

## CREE \$


LED MK-R

FWHM Asymmetric

Efficiency 89 %

Peak intensity 0.600 cd/lm

Required components:



## CREE ÷


LED XHP50

FWHM Asymmetric

Efficiency 90 %

Peak intensity 0.610 cd/lm

Required components:



## CREE \$


LED XM-L

FWHM Asymmetric

Efficiency 90 %

Peak intensity 0.700 cd/lm

Required components:




# CREE 💠

LED XP-L

FWHM Asymmetric

Efficiency 91 %

Peak intensity 0.700 cd/lm



# PRODUCT DATASHEET CA13752\_STRADA-SQ-FT

## PHOTOMETRIC DATA (MEASURED):

## CREE \$


LED XP-L2

FWHM Asymmetric

Efficiency 90 %

Peak intensity 0.660 cd/lm

Required components:



### **MUMILEDS**


LED LUXEON M/MX

FWHM Asymmetric

Efficiency 88 %

Peak intensity 0.620 cd/lm

Required components:



## **MATERIAL PROPERTY OF LUMILEDS**


LED LUXEON MZ

FWHM Asymmetric

Efficiency 90 %

Peak intensity 0.710 cd/lm

Required components:




## **DESCRIPTION** LUMILEDS

LED LUXEON XR-M linear 1x3, 1x4, 1x5

FWHM Asymmetric Efficiency 92 %

Peak intensity 0.650 cd/lm





# PRODUCT DATASHEET CA13752\_STRADA-SQ-FT

## PHOTOMETRIC DATA (MEASURED):


#### OSRAM Opto Semiconductors

LED Duris S10

FWHM Asymmetric

Efficiency 89 %

Peak intensity 0.610 cd/lm



# PRODUCT DATASHEET CA13752\_STRADA-SQ-FT


## PHOTOMETRIC DATA (SIMULATED):

CREE 💠

LED MX-3

FWHM Asymmetric

Efficiency 90 %
Peak intensity cd/lm
Required components:




CREE 🚓

LED MX-6

FWHM Asymmetric

Efficiency 90 %
Peak intensity cd/lm

Required components:




CREE 🕏

LED XM-L2

FWHM Asymmetric

Efficiency 90 %
Peak intensity cd/lm

Required components:




CREE 💠

LED XP-G2

FWHM Asymmetric

Efficiency 89 %
Peak intensity cd/lm
Required components:





# PRODUCT DATASHEET CA13752 STRADA-SQ-FT

## PHOTOMETRIC DATA (SIMULATED):


# CREE 💠

LED XP-G3 FWHM Asymmetric

Efficiency 76 %
Peak intensity 0.656 cd/lm

Required components:

Undefined Manufacturer: Protective Plate, Glass



## CREE 🕏

LED XP-L2


FWHM Asymmetric

Efficiency 76 %

Peak intensity 0.640 cd/lm

Required components:

Undefined Manufacturer: Protective Plate, Glass



## **UMILEDS**

LED LUXEON M/MX

FWHM Asymmetric Efficiency 78 %

Peak intensity 0.570 cd/lm

Required components:

Undefined Manufacturer: Protective Plate, Glass


#### OSRAM Opto Semiconductors

LED OSCONIQ P 7070

FWHM Asymmetric

Efficiency 89 %

Peak intensity 0.790 cd/lm





# PRODUCT DATASHEET CA13752 STRADA-SQ-FT

#### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

#### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### **LEDIL Oy**

Joensuunkatu 13 FI-24240 SALO Finland

#### LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

# Local sales and technical support

www.ledil.com/ where\_to\_buy

#### **Shipping locations**

Salo, Finland Hong Kong, China

#### **Distribution Partners**

www.ledil.com/ where to buy