



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## OLGA-W

~40° wide beam with flange. Assembly with holder and installation tape.


### TECHNICAL SPECIFICATIONS:

Dimensions	Ø 32.0 mm
Height	19.1 mm
Fastening	tape, pin
Colour	black
Box size	476 x 273 x 292 mm
Box weight	10 kg
Quantity in Box	792 pcs
ROHS compliant	yes ⓘ



### MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour
OLGA-W	Lens	PMMA	clear
OLGA-HLD	Holder	PC	black
SPUTNIK-TAPE3	Tape	PU tape	black






#### PHOTOMETRIC DATA (MEASURED):



**CREE** 

LED XD16  
 FWHM 32.0°  
 Efficiency 82 %  
 Peak intensity 2.500 cd/lm  
 Required components:





**CREE** 

LED XHP50.2  
 FWHM 42.0°  
 Efficiency 84 %  
 Peak intensity 1.590 cd/lm  
 Required components:





**CREE** 

LED XHP70  
 FWHM 44.0°  
 Efficiency 84 %  
 Peak intensity 1.400 cd/lm  
 Required components:



**CREE** 


LED XHP70.2  
 FWHM 44.0°  
 Efficiency 83 %  
 Peak intensity 1.400 cd/lm  
 Required components:





#### PHOTOMETRIC DATA (MEASURED):





LED XQ-E HI  
 FWHM 34.0°  
 Efficiency 85 %  
 Peak intensity 2.300 cd/lm  
 Required components:





LED LUXEON 5050  
 FWHM 35.0°  
 Efficiency 86 %  
 Peak intensity 2.200 cd/lm  
 Required components:



LED LUXEON CZ  
 FWHM 34.0°  
 Efficiency 86 %  
 Peak intensity 2.500 cd/lm  
 Required components:





LED LUXEON M/MX  
 FWHM 42.0°  
 Efficiency 84 %  
 Peak intensity 1.600 cd/lm  
 Required components:





#### PHOTOMETRIC DATA (MEASURED):





LED LUXEON V  
 FWHM 38.0°  
 Efficiency 84 %  
 Peak intensity 2.000 cd/lm  
 Required components:





LED Oslon Black Flat  
 FWHM 31.0°  
 Efficiency 85 %  
 Peak intensity 2.800 cd/lm  
 Required components:



LED Oslon Square EC  
 FWHM 39.0°  
 Efficiency 84 %  
 Peak intensity 1.900 cd/lm  
 Required components:





LED Oslon Square Gen3  
 FWHM 39.0°  
 Efficiency 85 %  
 Peak intensity 2.000 cd/lm  
 Required components:



### PHOTOMETRIC DATA (MEASURED):


**OSRAM**  
Opto Semiconductors

LED Oslon SSL 150  
FWHM 34.0°  
Efficiency 85 %  
Peak intensity 2.500 cd/lm  
Required components:




**SAMSUNG**

LED LH181B  
FWHM 30.0°  
Efficiency 85 %  
Peak intensity 2.800 cd/lm  
Required components:



**SAMSUNG**


LED LH351B  
FWHM 41.0°  
Efficiency 85 %  
Peak intensity 1.800 cd/lm  
Required components:



### PHOTOMETRIC DATA (SIMULATED):


#### CITIZEN

LED PSL440  
FWHM 42.0°  
Efficiency 94 %  
Peak intensity 2.030 cd/lm  
Required components:




#### CITIZEN

LED PSL445  
FWHM 47.0°  
Efficiency 90 %  
Peak intensity 1.545 cd/lm  
Required components:




#### CREE

LED XHP50  
FWHM 42.0°  
Efficiency 92 %  
Peak intensity 1.975 cd/lm  
Required components:



#### LUMILEDS

LED LUXEON MZ  
FWHM 33.0°  
Efficiency 93 %  
Peak intensity 3.060 cd/lm  
Required components:






## PHOTOMETRIC DATA (SIMULATED):



LED NFMW48xA  
FWHM 36.0°  
Efficiency 93 %  
Peak intensity 2.600 cd/lm  
Required components:



### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)