



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Laird Technologies

Web site: www.LairdTech.com

All Categories > Antennas & Reception Solutions > In-Building, CPE, Access Point, and Mobile Client Antennas > WLAN AP and Client Antennas > WLAN > Megasphere™ and Microsphere™ Infrastructure/In-building Antennas > Microsphere™ Infrastructure/In-building Antennas > Sphere™ Diveristy Infrastructure/In-building Antennas > Item # IOD2450-RT36



[larger image](#)

Item # IOD2450-RT36, Sphere™ Diveristy Infrastructure/In-building Antennas

[Stock Locator](#)

- Omnidirectional pattern provides optimal in-building coverage
- Ceiling mounted antenna available in 2400 MHz frequency range
- Quick installation with a standard ceiling tile frame metal clip
- Considerable gain improvement over traditional dipole antennas

Specifications

Model	2.4 GHz Sphere™ Diversity
Description	2.4 GHz Sphere™ Diversity
Frequency Range	2.4 - 2.5 GHz
Gain	3 dBi
Cable	36" RG-142
Connector Type	RP-TNC x 2
Max. Input Power	50 watts

[Print](#) [Back](#)