# imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



### **Sound Level Meters & Calibrator** Models 732A, 735, and CAL73

#### **Sound Level Meters**

Whether you are testing for OSHA compliance, quieting equipment, or monitoring the roar of a stadium crowd, B&K Precision's sound level meters can get the job done. The model 732A and 735 provide 30~130 dB capability in three convenient measurement ranges Low, Med, and Hi with an accuracy of  $\pm 1.5$  dB. The meter meets the IEC 651 Type II and includes frequency weighting A & C, and fast and slow time weighting. Two auxiliary ports provide either AC output, I Vrms full scale, or DC output, I0 mV/ dB. With the model 732A and 735, B&K Precision can meet all your sound testing needs.

#### Common Features (732A & 735)

- RS-232 Interface
- Bargraph
- MAX/MIN function
- Auto Ranging (30 ~ 130 dB)
- Resolution 0.1 dB
- Level Range Display
- AC/DC Signal Output
- Auto Power Off
- Backlit LCD

#### Features (735 only)

- Windows Software Included
- Clock Display
- 32,000 Records Data Logger



Back light function

**RS-232** Interface



included with model 735



732A

735

#### **Standard Acoustic Calibrator**

The CAL73 sound level calibrator is used to calibrate sound level meters and other sound measurement equipment. You can calibrate I inch diameter microphones directly and I/2 inch microphones using I/2 inch adapter supplied with the calibrator.

#### **Features**

- Conforms to IEC 60942 (2003) Class 2, ANSI SI.40-1984
- 94 dB and II4 dB Sound calibrator at I kHz
- Accurate and simple to use
- Fits I inch and ½ inch microphones



