



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





CRYSTEK
MICROWAVE
 A DIVISION OF CRYSTEK CORPORATION

RG-316 MMCX RF COAX CABLE ASSEMBLIES



RG316 50 Ohm MMCX Coaxial Cables

- MMCX / MMCX [Male Straight / Male Straight]
- MMCX / MMCX RA [Male Straight / Male Right Angle]
- MMCX RA / MMCX RA [Male Right Angle / Male Right Angle]
- SMA FB / MMCX [Female Bulk Head / Male Straight]
- SMA FB / MMCX RA [Female Bulkhead / Male Right Angle]

Actual Electrical Data:
 PN: CCMX-MM-RG316-12

Features:

- Bandwidth:** DC to 6 GHz
- Strain Relief:** Adhesive shrink tubing over crimp area
- Center Conductor:** [7/.0067"] SCCS (Silver Coated Copper Covered Steel)
- Shielding:** SPC (Silver-Plated Copper)
- Insulation:** PTFE (Polytetrafluoroethylene) dielectric
- Cable Outer Diameter:** 0.098" (2.49mm)
- Jacket:** FEP (Fluorinated Ethylene Propylene)
- Connector:** Gold-plated brass
- Operating Temperature:** -40°C to +85°C
- Minimum Bend Radius:** 0.5"

Freq. (MHz)	Insertion Loss
50	-0.36
500	-0.40
1000	-0.45
2000	-0.55
3000	-0.60
4000	-0.72
5000	-0.79
6000	-0.86

Custom Lengths Available

(Minimum Order Quantity Required)



MMCX / MMCX [Male Straight / Male Straight]

Part Number	Description	Length
CCMX-MM-RG316-6	RG316 Shielded Cable, MMCX Male STR / Male STR	6"
CCMX-MM-RG316-12	RG316 Shielded Cable, MMCX Male STR / Male STR	12"
CCMX-MM-RG316-18	RG316 Shielded Cable, MMCX Male STR / Male STR	18"
CCMX-MM-RG316-24	RG316 Shielded Cable, MMCX Male STR / Male STR	24"



CRYSTEK
 CORPORATION

12730 COMMONWEALTH DRIVE • FORT MYERS, FL 33913
 PHONE: 239-561-3311 • 800-237-3061 Rev.: A
 FAX: 239-561-1025 • WWW.CRYSTEK.COM Date: 03-01-14



CRYSTEK
MICROWAVE
 A DIVISION OF CRYSTEK CORPORATION

**RG-316 MMCX
 RF COAX CABLE
 ASSEMBLIES**



MMCX / MMCX RA [Male Straight / Male Right Angle]

Part Number	Description	Length
CCMX1-MM-RG316-6	RG316 Shielded Cable, MMCX Male STR / Male RA	6"
CCMX1-MM-RG316-12	RG316Shielded Cable, MMCX Male STR / Male RA	12"
CCMX1-MM-RG316-18	RG316 Shielded Cable, MMCX Male STR / Male RA	18"
CCMX1-MM-RG316-24	RG316 Shielded Cable, MMCX Male STR / Male RA	24"

MMCX RA / MMCX RA [Male Right Angle / Male Right Angle]

Part Number	Description	Length
CCMX2-MM-RG316-6	RG316 Shielded Cable, MMCX Male RA / Male RA	6"
CCMX2-MM-RG316-12	RG316 Shielded Cable, MMCX Male RA / Male RA	12"
CCMX2-MM-RG316-18	RG316 Shielded Cable, MMCX Male RA / Male RA	18"
CCMX2-MM-RG316-24	RG316 Shielded Cable, MMCX Male RA / Male RA	24"

SMA FB / MMCX [Female Bulk Head / Male Straight]

Part Number	Description	Length
CCSMX-FBM-RG316-6	RG316 Shielded Cable, SMA Female Bulkhead / MMCX Male STR	6"
CCSMX-FBM-RG316-12	RG316 Shielded Cable, SMA Female Bulkhead / MMCX Male STR	12"
CCSMX-FBM-RG316-18	RG316 Shielded Cable, SMA Female Bulkhead / MMCX Male STR	18"
CCSMX-FBM-RG316-24	RG316 Shielded Cable, SMA Female Bulkhead / MMCX Male STR	24"

SMA FB / MMCX [Female Bulk Head / Male Right Angle]

Part Number	Description	Length
CCSMX1-FBM-RG316-6	RG316 Shielded Cable, SMA Female Bulkhead / MMCX Male RA	6"
CCSMX1-FBM-RG316-12	RG316 Shielded Cable, SMA Female Bulkhead / MMCX Male RA	12"
CCSMX1-FBM-RG316-18	RG316 Shielded Cable, SMA Female Bulkhead / MMCX Male RA	18"
CCSMX1-FBM-RG316-24	RG316 Shielded Cable, SMA Female Bulkhead / MMCX Male RA	24"



CRYSTEK
 CORPORATION

12730 COMMONWEALTH DRIVE • FORT MYERS, FL 33913
 PHONE: 239-561-3311 • 800-237-3061 Rev.: A
 FAX: 239-561-1025 • WWW.CRYSTEK.COM Date: 03-01-14