

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



*NOTE: PICTURE FOR REFERENCE ONLY.

Punch Drive Adapter for CT-2920/CCP, CT-3001/CCP, CT-920CH/CCP

NOTES, UNLESS OTHERWISE SPECIFIED:

• Punch drive adapters holes to be punched in sheet metal with minimal burrs. Go to www.panduit.com for more information.

Size Chart:

Consult table below to select appropriate punch adapter required for the appropriate hole size, sheet metal thickness and Panduit Tool:

Panduit P/N	Largest Hole Size	Thickest Sheet Metal	Compatible with Panduit Tool(s)	
CD-2001-PDA	2" (50mm)	10 Gauge (3.42 mm) CT-3001/CCP		
	Conduit Size	mild steel	C1-3001/CCF	
CD-920-PDA	5-5/8" (144mm)	10 Gauge (3.42 mm),	CT-2920/CCP, CT-920CH/CCP	
	Dia. Round	mild steel		

Technical Information:

Panduit P/N	Weight	Punch Adapter Dims
CD-2001-PDA	4.6 lbs (2.1 kg)	6.6" L X 3.3" H X 2.1" W
	, , , ,	[168 L X 83 H X 54 W] mm
CD-920-PDA	5.1 lbs (2.3 kg)	7.5" L X 3.3" H X 2.1" W
	, , , ,	[191 L X 83 H X 54 W] mm

Each box contains one punch adapter, one 3/4" threaded stud, one pilot hole drill and one spacer. Can be used with standard Greenlee Hole Punches.

							CD-2001-PDA and CD-920-PDA Punch Drive Adapters
							CUSTOMER DRAWING
							TTEM REVISION NAME: 00084SMU_DC/00 PANDUT
							UNLESS OTHERWISE SPECIFIED, MATERIAL: DIMENSIONAL TOLERANCES ARE:
01	10-14-16	ACC	RAKL	JADE	CORRECTED PART NUMBERS	010819	(.x) ± (.xxx) ± (.xxx) ±
00	9-12-16	ACC	BKA	JADE	DRAWING RELEASED	010062	THIRD ANGLE DRAWING NUMBER: 00084SMU_DC
REV	DATE	ВҮ	СНК	APR	DESCRIPTION	ECN	DRAWN BY: DATE: CHK BKA SCALE NONE SHT 1 OF 1 B