



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Features

- Lead free
- RoHS compliant*
- Surface Mount SMC package
- Standoff Voltage: 5.0 to 170 volts
- Power Dissipation: 1500 watts



Model CD214C is currently available, although not recommended for new designs. [Model SMCJ](#) is preferred.

CD214C Transient Voltage Suppressor Diode Series

General Information

The markets of portable communications, computing and video equipment are challenging the semiconductor industry to develop increasingly smaller electronic components.

Bourns offers Transient Voltage Suppressor Diodes for surge and ESD protection applications, in compact chip package DO-214AB (SMC) size format. The Transient Voltage Suppressor series offers a choice of Working Peak Reverse Voltage from 5 V up to 170 V and Breakdown Voltage up to 200 V. Typical fast response times are less than 1.0 ns for unidirectional devices and less than 5.0 ns for bidirectional devices from 0 V to Minimum Breakdown Voltage.

Bourns® Chip Diodes conform to JEDEC standards, are easy to handle with standard pick and place equipment and the flat configuration minimizes roll away.

Electrical Characteristics (@ T_A = 25 °C Unless Otherwise Noted)

| Parameter | Symbol | Value | Unit |
|--|--------------------|-------------------------|-------|
| Minimum Peak Pulse Power Dissipation (T _P = 1 ms) <small>(Note 1,2)</small> | P _{PK} | 1500 | Watts |
| Peak Forward Surge Current 8.3ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method) <small>(Note 3)</small> | I _{FSM} | 200 | Amps |
| Steady State Power Dissipation @ T _L = 75 °C | P _{M(AV)} | 5.0 | Watts |
| Maximum Instantaneous Forward Voltage @ I _{PP} = 100 A (For Unidirectional Units Only) | V _F | <small>(Note 5)</small> | Volts |
| Operating Temperature Range | T _J | -55 to +150 | °C |
| Storage Temperature Range | T _{STG} | -55 to +175 | °C |

1. Non-repetitive current pulse, per Pulse Waveform graph and derated above T_A = 25 °C per Pulse Derating Curve.
2. Thermal Resistance Junction to Lead.
3. 8.3 ms Single Half-Sine Wave duty cycle = 4 pulses maximum per minute (unidirectional units only).
4. Single Phase, Half Wave, 60 Hz, resistive or inductive load. For capacitive load, derate current by 20 %.
5. V_F = 3.5 V on CD214C-T5.0A through CD214C-T90A and V_F = 5.0 V on CD214C-T100A through CD214C-T170A.

How To Order

| | |
|---|------------------------------|
| | CD 214C - T 5.0 CA LF |
| Common Code _____ | |
| Chip Diode _____ | |
| Package _____ | |
| 214A = SMA/DO-214AC | |
| 214B = SMB/DO-214AA | |
| 214C = SMC/DO-214AB | |
| Model _____ | |
| T = Transient Voltage Suppressor Series | |
| Working Peak Reverse Voltage _____ | |
| 5.0 = 5.0 V _{RWM} (Volts) | |
| 170 = 170 V _{RWM} (Volts) | |
| Suffix _____ | |
| A = 5 % Tolerance Device | |
| CA = 5 % Tolerance Bidirectional Device | |
| Terminations _____ | |
| LF = 100 % Sn (lead free) | |



Asia-Pacific:
Tel: +886-2 2562-4117 • Fax: +886-2 2562-4116

Europe:
Tel: +41-41 768 5555 • Fax: +41-41 768 5510

The Americas:
Tel: +1-951 781-5500 • Fax: +1-951 781-5700

www.bourns.com

Compliance

- IEC 61000-4-2 ESD (Min. Level 4)
- IEC 61000-4-4 EFT
- IEC 61000-4-5 Surge

CD214C Transient Voltage Suppressor Diode Series

BOURNS®

Electrical Characteristics (@T_A = 25 °C unless otherwise noted)

| Unidirectional Device | | Bidirectional Device | | Breakdown Voltage V _{BR} (Volts) | | | Working Peak Reverse Voltage | Maximum Reverse Leakage @ V _{RWM} | Maximum Reverse Voltage @ I _{RSM} | Maximum Reverse Surge Current |
|-----------------------|-----------------|----------------------|-----------------|--|-------|-----------------------|------------------------------------|---|---|--|
| Part Number | Part Marking | Part Number | Part Marking | Min. | Max. | @ I _T (mA) | V _{RWM} (Volts) | I _R (µA) | V _{RSM} (Volts) | I _{RSM} (Amps) |
| CD214C-T5.0A | GDE | CD214C-T5.0CA | BDE | 6.4 | 7.23 | 10 | 5 | 1000 | 9.2 | 163 |
| CD214C-T6.0A | GDG | CD214C-T6.0CA | BDG | 6.67 | 7.67 | 10 | 6 | 1000 | 10.3 | 145.6 |
| CD214C-T6.5A | GDK | CD214C-T6.5CA | BDK | 7.22 | 8.3 | 10 | 6.5 | 500 | 11.2 | 133.9 |
| CD214C-T7.0A | GDM | CD214C-T7.0CA | BDM | 7.78 | 8.95 | 10 | 7 | 200 | 12 | 125 |
| CD214C-T7.5A | GDP | CD214C-T7.5CA | BDP | 8.33 | 9.58 | 1 | 7.5 | 100 | 12.9 | 116.3 |
| CD214C-T8.0A | GDR | CD214C-T8.0CA | BDR | 8.89 | 10.2 | 1 | 8 | 50 | 13.6 | 110.3 |
| CD214C-T8.5A | GDT | CD214C-T8.5CA | BDT | 9.44 | 10.8 | 1 | 8.5 | 20 | 14.4 | 104.2 |
| CD214C-T9.0A | GDV | CD214C-T9.0CA | BDV | 10 | 11.5 | 1 | 9 | 10 | 15.4 | 97.4 |
| CD214C-T10A | GDY | CD214C-T10CA | BDY | 11.1 | 12.8 | 1 | 10 | 5 | 17 | 88.2 |
| CD214C-T11A | GDZ | CD214C-T11CA | BDZ | 12.2 | 14.4 | 1 | 11 | 5 | 18.2 | 82.4 |
| CD214C-T12A | GEE | CD214C-T12CA | BEE | 13.3 | 15.3 | 1 | 12 | 5 | 19.9 | 75.3 |
| CD214C-T13A | GEG | CD214C-T13CA | BEG | 14.4 | 16.5 | 1 | 13 | 5 | 21.5 | 69.7 |
| CD214C-T14A | GEK | CD214C-T14CA | BEK | 15.6 | 17.9 | 1 | 14 | 5 | 23.2 | 64.7 |
| CD214C-T15A | GEM | CD214C-T15CA | BEM | 16.7 | 19.2 | 1 | 15 | 5 | 24.4 | 61.5 |
| CD214C-T16A | GEP | CD214C-T16CA | BEP | 17.8 | 20.5 | 1 | 16 | 5 | 26 | 57.7 |
| CD214C-T17A | GER | CD214C-T17CA | BER | 18.9 | 21.7 | 1 | 17 | 5 | 27.6 | 53.3 |
| CD214C-T18A | GET | CD214C-T18CA | BET | 20 | 23.3 | 1 | 18 | 5 | 29.2 | 51.4 |
| CD214C-T20A | GEV | CD214C-T20CA | BEV | 22.2 | 25.5 | 1 | 20 | 5 | 32.4 | 46.3 |
| CD214C-T22A | GEX | CD214C-T22CA | BEX | 24.4 | 28 | 1 | 22 | 5 | 35.5 | 42.2 |
| CD214C-T24A | GEZ | CD214C-T24CA | BEZ | 26.7 | 30.7 | 1 | 24 | 5 | 38.9 | 38.6 |
| CD214C-T26A | GFE | CD214C-T26CA | BFE | 28.9 | 32.2 | 1 | 26 | 5 | 42.1 | 35.6 |
| CD214C-T28A | GFG | CD214C-T28CA | BFG | 31.1 | 35.8 | 1 | 28 | 5 | 45.4 | 33 |
| CD214C-T30A | GFK | CD214C-T30CA | BFK | 33.3 | 38.3 | 1 | 30 | 5 | 48.4 | 31 |
| CD214C-T33A | GFM | CD214C-T33CA | BFM | 36.7 | 42.2 | 1 | 33 | 5 | 53.3 | 28.1 |
| CD214C-T36A | GFP | CD214C-T36CA | BFP | 40 | 46 | 1 | 36 | 5 | 58.1 | 25.8 |
| CD214C-T40A | GFR | CD214C-T40CA | BFR | 44.4 | 51.1 | 1 | 40 | 5 | 64.5 | 23.3 |
| CD214C-T43A | GFT | CD214C-T43CA | BFT | 47.8 | 54.9 | 1 | 43 | 5 | 69.4 | 21.6 |
| CD214C-T45A | GFV | CD214C-T45CA | BFV | 50 | 57.5 | 1 | 45 | 5 | 72.7 | 20.6 |
| CD214C-T48A | GFX | CD214C-T48CA | BFX | 53.3 | 61.3 | 1 | 48 | 5 | 77.4 | 19.4 |
| CD214C-T51A | GFZ | CD214C-T51CA | BFZ | 56.7 | 65.2 | 1 | 51 | 5 | 82.4 | 18.2 |
| CD214C-T54A | GGE | CD214C-T54CA | BGE | 60 | 69 | 1 | 54 | 5 | 87.1 | 17.2 |
| CD214C-T58A | GGG | CD214C-T58CA | BGG | 64.4 | 74.6 | 1 | 58 | 5 | 93.6 | 16 |
| CD214C-T60A | GGK | CD214C-T60CA | BGK | 66.7 | 76.7 | 1 | 60 | 5 | 96.8 | 15.5 |
| CD214C-T64A | GGM | CD214C-T64CA | BGM | 71.1 | 81.8 | 1 | 64 | 5 | 103 | 14.6 |
| CD214C-T70A | GGP | CD214C-T70CA | BGP | 77.8 | 89.5 | 1 | 70 | 5 | 113 | 13.3 |
| CD214C-T75A | GGR | CD214C-T75CA | BGR | 83.3 | 95.8 | 1 | 75 | 5 | 121 | 12.4 |
| CD214C-T78A | GGT | CD214C-T78CA | BGT | 86.7 | 99.7 | 1 | 78 | 5 | 126 | 11.4 |
| CD214C-T85A | GGV | CD214C-T85CA | BGV | 94.4 | 108.2 | 1 | 85 | 5 | 137 | 10.4 |
| CD214C-T90A | GGX | CD214C-T90CA | BGX | 100 | 115.5 | 1 | 90 | 5 | 146 | 10.3 |
| CD214C-T100A | GGZ | CD214C-T100CA | BGZ | 111 | 128 | 1 | 100 | 5 | 162 | 9.3 |
| CD214C-T110A | GHE | CD214C-T110CA | BHE | 122 | 140 | 1 | 110 | 5 | 177 | 8.4 |
| CD214C-T120A | GHG | CD214C-T120CA | BHG | 133 | 153 | 1 | 120 | 5 | 193 | 7.9 |
| CD214C-T130A | GHK | CD214C-T130CA | BHK | 144 | 165 | 1 | 130 | 5 | 209 | 7.2 |
| CD214C-T150A | GHM | CD214C-T150CA | BHM | 167 | 192 | 1 | 150 | 5 | 243 | 6.2 |
| CD214C-T160A | GHP | CD214C-T160CA | BHP | 178 | 205 | 1 | 160 | 5 | 259 | 5.8 |
| CD214C-T170A | GHR | CD214C-T170CA | BHR | 189 | 217.5 | 1 | 170 | 5 | 275 | 5.5 |


Notes:

1. Suffix 'A' denotes a 5 % tolerance device.
2. Suffix 'CA' denotes a 5 % tolerance bidirectional device.
3. For bidirectional devices with a V_R of 10 volts or less, the I_R limit is double.
4. For unidirectional devices with a V_F max. of 3.5 V at an I_F of 35 A, 0.5 Sine Wave of 8.3 ms Pulse Width.

CD214C Transient Voltage Suppressor Diode Series




Product Dimensions



| Dimension | SMC (DO-214AB) |
|-----------|---------------------------------------|
| A | $\frac{6.60 - 7.11}{(0.260 - 0.280)}$ |
| B | $\frac{5.59 - 6.22}{(0.220 - 0.245)}$ |
| C | $\frac{2.92 - 3.18}{(0.115 - 0.125)}$ |
| D | $\frac{0.15 - 0.31}{(0.006 - 0.112)}$ |
| E | $\frac{7.75 - 8.13}{(0.305 - 0.320)}$ |
| F | $\frac{0.05 - 0.20}{(0.002 - 0.008)}$ |
| G | $\frac{2.01 - 2.62}{(0.080 - 0.103)}$ |
| H | $\frac{0.76 - 1.52}{(0.030 - 0.060)}$ |

DIMENSIONS: $\frac{\text{MM}}{\text{(INCHES)}}$

Recommended Pad Layout



| Dimension | SMC (DO-214AB) |
|-----------|------------------------|
| A (Max.) | $\frac{4.69}{(0.185)}$ |
| B (Min.) | $\frac{3.07}{(0.121)}$ |
| C (Min.) | $\frac{1.52}{(0.060)}$ |

DIMENSIONS: $\frac{\text{MM}}{\text{(INCHES)}}$

Physical Specifications


CaseMolded plastic per UL Class 94V-0
 Polarity.....Cathode band indicates unidirectional device
 No cathode band indicates bidirectional device
 Weight0.007 ounces / 0.21 grams

CD214C Transient Voltage Suppressor Diode Series




Rating and Characteristic Curves


Pulse Derating Curve




Maximum Non-Repetitive Surge Current




Pulse Waveform




Typical Junction Capacitance



Pulse Rating Curve



Steady State Power Derating Curve




Specifications are subject to change without notice. Customers should verify actual device performance in their specific applications.

CD214C Transient Voltage Suppressor Diode Series

BOURNS®

Packaging Information

The product will be dispensed in Tape and Reel format (see diagram below).



Devices are packed in accordance with EIA standard RS-481-A and specifications shown here.

| Item | Symbol | SMC (DO-214AB) |
|------------------------|----------------|--|
| Carrier Width | A | $\frac{7.22 \pm 0.10}{(0.284 - 0.004)}$ |
| Carrier Length | B | $\frac{8.11 \pm 0.10}{(0.319 - 0.004)}$ |
| Carrier Depth | C | $\frac{2.36 \pm 0.10}{(0.093 - 0.004)}$ |
| Sprocket Hole | d | $\frac{1.55 \pm 0.05}{(0.061 - 0.002)}$ |
| Reel Outside Diameter | D | $\frac{330}{(12.992)}$ |
| Reel Inner Diameter | D ₁ | $\frac{50.0}{(1.969)}$ MIN. |
| Feed Hole Diameter | D ₂ | $\frac{13.0 \pm 0.20}{(0.512 - 0.008)}$ |
| Sprocket Hole Position | E | $\frac{1.75 \pm 0.10}{(0.069 - 0.004)}$ |
| Punch Hole Position | F | $\frac{7.50 \pm 0.10}{(0.295 - 0.004)}$ |
| Punch Hole Pitch | P | $\frac{4.00 \pm 0.10}{(0.157 - 0.004)}$ |
| Sprocket Hole Pitch | P ₀ | $\frac{4.00 \pm 0.10}{(0.157 - 0.004)}$ |
| Embossment Center | P ₁ | $\frac{2.00 \pm 0.10}{(0.079 - 0.004)}$ |
| Overall Tape Thickness | T | $\frac{0.30 \pm 0.10}{(0.012 - 0.004)}$ |
| Tape Width | W | $\frac{16.00 \pm 0.20}{(0.630 - 0.008)}$ |
| Reel Width | W ₁ | $\frac{22.4}{(0.882)}$ MAX. |
| Quantity per Reel | -- | 3,000 |