

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









CDB260 Series 260 W



Startup

Time

260 W Programmable Constant Current LED Driver with 0-10 V Dimming & Integrated Bluetooth® Mesh

Avi-on App	120/277 Vac nominal	260 W	up to 93% typical	90°C (measured at the hot spot)	< 20% (from 100% to 50% of max rated power		> 0.9 (from 100% to 50% of max rated power)		0 - 10\ 1 -1009 (% of lo	500 n	
			Ordering Part Number		Nominal Input Voltage (Vac)	Max Output lout 1 Power (mA)		Vout 1 (Vdc)	lout 2 (mA)	Vout 2 (Vdc)	
Jan				CDB260W-08	860-400-	120/277	260	430 to 860	234 to 300	325 to 650	312 to 400

CDB260W-1300-280-

CDB260W-1700-210-



120/277

120/277

- · W: Wire whip antenna
- R: Removable external antenna connected to RPSMA connector

260

260

PROGRAMMING

- Dual output voltage range selection
- Serial port programming
 - Current: 100% to 50% in each voltage range
 - Data log read: SKU, S/N, lot code, hours of operation, FW rev., fault events: power failure, transients (short or surge), thermal

650 to 1300 | 156 to 200 | 465 to 930 | 218 to 280

850 to 1700 117 to 150 620 to 1240 164 to 210

COMMUNICATION

- Bi-directional (dimming ↑ and ↓ and data log read)
- Bluetooth Mesh with wire whip antenna and external removable antenna
 Bluetooth

AVI-ON BLUETOOTH MESH SOLUTION

- Wireless lighting controls with simple set-up that anyone can use
- Pre-integrated Bluetooth Smart + CSRmesh module enables brands to create multi-way controls and switching without additional wiring; no central gateway required
- · Utility grade, secure, reliable mobile app & software
- Dimming, grouping, many users, schedules, timers
- · Virtually unlimited range with mesh
- · Download for free, additional services available
- Compatible with large ecosystem of products from major brands
- Avi-on battery-powered movable dimming switches available to complete the turnkey solution














with 0-10 V Dimming & Integrated Bluetootl | Input Voltage | Max. Output Power | Efficiency Power Femperature | THD | Power Factor | Dimming Type and Range | Dimming Type | Compand Range | Dimming Type | Compand Range | C



FEATURES

- Non-linear 0-10V dimming profile with dim-to-off
- · Auxiliary output 12 V/100 mA
- · IP66-rated case with silicone-based potting
- · Outdoor Surge protection:
 - IEC61000-4-5: 4 kV line to line/4 kV line to earth
 - 2.5 kV ring wave: ANSI/IEEE c62.41.1-2002 & c62.41.2-2002 category A
- Conducted and radiated EMI: Compliant with FCC CFR Title 47 Part 15 Class A at 120 Vac & 277 Vac
- Lifetime: 50,000 hours @ Tc = 70°C
- 90°C maximum case hot spot temperature
- UL Class P

APPLICATIONS

- Outdoor & Indoor
 Horticulture grow lights
- Street lights, Area lights

Aluminum Case L 217/240.5 x W 50.8 x H 38.5 mm

(L 8.54/9.47 x W 2.00 x H 1.52 in)

· Horticulture grow lights · Industrial high-bay lights

CHINA Operations

tel: +86-756-6266298 No. 8 Pingdong Road 2 Zhuhai, Guangdong, China 519060

www.erp-power.com

SaveEnergy@erp-power.com

USA Headquarters

tel: +1-805-517-1300 893 Patriot Drive, Suite E Moorpark, CA 93021, USA