

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







PRODUCT BRIEF:

Logic PD :: Marvell

PXA270 CARD ENGINE System on Module

The PXA270 Card Engine is a compact, product-ready hardware and software solution that fast forwards your embedded product design.

The PXA270 Card Engine is a complete System on Module (SOM) that offers essential features for handheld and embedded networking applications. Use of custom baseboards makes the Card Engine the ideal foundation for OEMs developing handheld and compact products. The Card Engine provides a common reference pin-out on its expansion connectors, which enables easy scalability to next generation microprocessor Card Engines when new functionality or performance is required.

Application development is performed right on the product-ready PXA270 Card Engine and software Board Support Packages (BSPs), which enables you to seamlessly transfer your application code and hardware into production.

The PXA270 Card Engine is ideal for applications in the medical, point-of-sale, industrial, and security markets. From patient



PXA270 CARD ENGINE

monitoring and medical imaging, to card payment terminals and bar code readers, to CCTV cameras and intruder alarms, the PXA270 Card Engine allows for powerful versatility and long-life products.

PXA270 CARD ENGINE :: HIGHLIGHTS:


- +Product-ready System on Module with the Marvell PXA270 Applications Processor running at 416 or 520 MHz
- +Compact form factor 60.2 mm x 67.8 mm x 4.4 mm
- +Long product lifecycle
- +0 °C to 70 °C (commercial temp) or -25 °C to 85 °C (extended temp)
- +RoHS compliant

PXA270 ZOOM™ SDK :: FEATURES:

- +Application baseboard
- +PXA270 Card Engine (CENGPXA270-520-10-504HCR)
- + Necessary accessories to immediately get up and running
- +Kit available from Logic PD (SDK-PXA270-520-10-6432R)
- +See Zoom™ SDK product brief for more information



PXA270 Card Engine Block Diagram



PXA270 Card Engine Ordering Information

Logic PD Model Number	Speed (MHz)	SDRAM (MB)	NAND Flash (MB)	NOR Flash (MB)	Touch	Audio	Ethernet	Temp (°C)
CENGPXA270-416-11-505EXR	416	64	0	64	Υ	Υ	_	-25 – 85
CENGPXA270-416-11-505HXR	416	64	0	64	Υ	Υ	Υ	-25 – 85
CENGPXA270-520-11-504HCR	520	64	0	32	Υ	Υ	Υ	0 – 70

PXA270 ZOOM™ SDK Ordering Information¹

Logic PD Model Number	SOM Configuration	Recommended Resale
SDK-PXA270-520-10-6432R	CENGPXA270-520-10-504HCR	\$499

^{1.} The SDK contains a PXA270-10 Card Engine; quantities are limited.

LOGIC PD WEBSITE :: DESIGN RESOURCES:

- +Logic PD Products : www.logicpd.com/products
- +Logic PD Technical Support : www.logicpd.com/product-support
- +For more information contact Logic PD Sales: product.sales@logicpd.com





Product Features

Processor

+Marvell PXA270 Applications Processor running at 416 or 520 MHz

SDRAM Memory

+64 MB SDRAM standard

Flash Memory

+32 or 64 MB NOR standard

Display

- +Programmable color LCD controller
- +Built-in driver supports up to 800x600 with 16-bit LCD interface

Touch Screen

+Integrated 4-wire touch screen controller

Network Support

+10/100 Base-T Ethernet controller for application/debug (SMSC LAN 91C111)

Audio

+AC97audio codec

PC Card Expansion

- +CompactFlash Type I card (memory-mapped mode only)
- +Smart Card, MMC/SD, dual PCMCIA interfaces

USB

+USB 2.0 full-speed host and device interface

Serial Ports

+Three 16C550 compatible UARTs, two I2C

IrD∆

+SIR supports up to 115.2 Kbps, multiplexed IrDA/Bluetooth

GPIO

+Programmable I/O depending on peripheral requirements

Software

- +LogicLoader™ (bootloader/monitor)
- +Windows Embedded CE 5.0 BSP

Mechanical

+60.2 mm wide x 67.8 mm long x 4.4 mm high

RoHS Compliant

PN: 1001781 Rev E