

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China








THIS DRAWING AND THE INFORMATION SET FORTH HEREON ARE THE PROPERTY OF TYCO ELECTRONICS CORPORATION AND ARE TO BE HELD IN TRUST AND CONFIDENCE. PUBLICATION, DUPLICATION, DUPLICATION, DUPLICATION, DISCLOSURE OR USE FOR ANY PURPOSE NOT EXPRESSLY AUTHORIZED IN WRITING BY TYCO ELECTRONICS CORPORATION IS PROHIBITED.

| Maintenance of the content of the co



1.41

35,82

. 41

35,82

48,

4,10 [[104]

2, 72 1[ 69, 09]

91 52

[19

. 75 [19, 05

1,10 27,94 1,56

[39,6<u>2</u>

2, 90 73, 60

## NOTES:

CES-2-T1-XX

CES-2-T1B-XX

CES-3-T1-XX

CES-4-T1-XX

CES-5-T4-XX

THE LAST "XX" IN THE PART NUMBER DESIGNATES MATERIAL AS SHOWN BELOW:
"AL": ALUMINUM 6061 T-6 WITH FINISH OF HARD ANODIZE PER MIL-A-8625, TYPE III,
CLASS 2, DYED BLACK.

"SS": STAINLESS STEEL TYPE 316, WITH FINISH OF PASSIVATE PER QQ-P-35, OR MIL-S-5002 FOR STANDARD BLACK NYLON MATERIAL, OMIT THE LAST "XX" IN THE PART NUMBER.

40

60 15,24]

, 90 22, 86

<del>.</del> 25

[4,31

, 30 , [ <u>7, 62</u>

.50 [12]

60 17 5,24][4,31

[10]

A HEAT SHRINKABLE BOOT MATERIAL IN ACCORDANCE WITH -3 POLYOLEFIN

PART TO BE MARKED AS SHOWN, REPLACE X'S WITH APPROPRIATE CHARACTERS. (e.g. CES-2-T1-AL).

4. THIS PART IS DESIGNED TO FIT THROUGH A PANEL OR BULKHEAD WITH A MAXIMUM WALL THICKNESS AS INDICATED IN TABLE.

4. FACTORY APPLIED HOT MELT ADHESIVE IS STANDARD.


1-12 UNF

1-12 UNF

3/8-12 UNF

2-8 UN

3 3/8-8 UN



1/4 6,35

1/4 6,35

<u>6,</u>35

3/8 9,65

21 33]

88]

(88°

[7,88]

[5,

2,75 [69,85]

2,75 [<u>69,85]</u>

3,15 [80,01]

4,50 114,30