



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



- * LVDS Output
- * Industry Standard Outline

- Applications**
- * Serial Communications
 - * Routers
 - * Switches
 - * WAN Interfaces
 - * Test Equipment




Part Numbering Example: CFVL Z - A5 BP - 222.5792 TS

| CFVL | Z | A5 | BP | 222.5792 | TS |
|--------|-----------------------------------|---|----------------------------------|-----------|----------------|
| SERIES | PACKAGING OPTIONS | OPERATING TEMP. | STABILITY | FREQUENCY | TRI-STATE |
| CFVL | Blank = Bulk Z = Tape and Reel | Blank = 0°C ~ +70°C A5 = -20°C ~ +70°C A7 = -40°C ~ +85°C | Blank = ±100 ppm BP = ±50 ppm | | TS = Tri-State |

| Specifications: | Min | Typ | Max | Unit |
|---|---------------------------------|-------|-----------|--------|
| Frequency Range: | 38 | | 640 | MHz |
| Stability: | -50 | | + 50 | ppm |
| Supply Voltage: | 3.135 | 3.3 | 3.465 | V |
| Frequency Tuning Range: | | ± 100 | | ppm |
| External Control Voltage: | 0.35 | | 3.0 | V |
| Operating Temperature: | -40 | | + 85 | °C |
| Storage Temperature: | -55 | | + 125 | °C |
| Duty Cycle: | 45 | | 55 | % |
| Start-Up Time: | | 3 | 10 | mS |
| Aging: (ppm/1st Year) Ta=25C, Vdd=3.3V | | | 5 | ppm |
| Supply Current: | | | 100 | mA |
| Short Circuit Current: | | ± 50 | | mA |
| RMS Period Jitter: | | 5 | | pS |
| RMS Integrated Jitter: 12kHz to 20MHz | | 0.7 | | pS |
| Phase Noise @ 10kHz: | | | -120 | dBc/Hz |
| Output Voltage: Voh Vol | Vdd - 0.9 | | Vdd - 1.6 | V |
| Output Differential Voltage: | 247 | 355 | 454 | mV |
| Rise/Fall Time: | | 0.4 | 0.8 | nS |
| Output Level: | LVDS | | | |
| Packaging: | Tape and Reel 1000 pcs per Reel | | | |

CFVL

Dimensions are in mm



- PIN Function
- 1 VCONTROL
 - 2 ENABLE
 - 3 Ground
 - 4 LVDS +
 - 5 LVDS -
 - 6 Vdd

LVDS Levels Test Circuit

