mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



PRODUCT DATASHEET

NiMH Battery Charger (CHFCV)

EASY

- LED charge indicators
- Includes charge status indicators

NOTE: Batteries must be charged in pairs according to specific battery sizes.

VERSATI LE

- Charges multiple combinations of AAA, AA, C, D or 9V NiMH batteries overnight
- Charges up to 4 AA or AAA NiMH batteries at a time.

SAFETY FEATURES

 Reverse polarity protection protects the charger and batteries against damage from incorrectly installed batteries.





Before Using Your Charger: Please read all instructions and cautionary markings on the battery charger, batteries, and device.

Best used with Energizer NiMH batteries.

North American Region Download Instructions and Warranty Information

English | Français | Español

Product Detail:

Designation: Family Charger Color: Gun Metal Gray LISTED

Ch. ging Capability: 2 or 4 "AA" Batteries NOT Satteries must be ch. d in pairs according specific battery sizes. 2 or 4 "AA" Batteries 2 or 4 "C/D" Batteries 1 or 2 "9V" Batteries

Chai, ing Current: "AA/AAA" 200 mA "C/D" 200 mA "9V" 16 mA Trickle Charge: "AA-AAA-C-D" 15-25 mA

Charging Time:	Battery	Capacity	Estimated
(estimated)	(NiMH)	(mAh)	(time)
	AA		11.0-13.0 hrs
	AA	2100-2500	15.0-16.5 hrs
	AAA	600-800	4.5-5.0 hrs
	C/D	2300-2600	16.5 hrs
	9V	110-150	10.0-13.5 hrs

 Shutoff Mechanism:
 Timer Control

 Max Timer Control
 16.5 hours

 Weight (charger):
 500 grams (17.7 oz.)

 Dimensions (mm):
 52 x 204 x 100 (H x L x W)

Safety Features: Reverse Polarity Protection Safety Timer to Prevent Over Charge

Important Notice

This datasheet contains information specific to products manufactured at the time of its publication. © Energizer Holdings, I nc. Contents herein do not constitute a warranty.



