



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Asia Pacific Region
[Download Instructions](#)

Easy Charger

SAFE

- Safety on/off switch



EASY

- Convenient displays tell when charge is complete



ECONOMICAL

- Batteries can be charged hundreds of times



Before Using Your Charger:
 Please read all instructions and cautionary markings on the battery charger, batteries, and device.

Product Detail:

Designation: Easy Charger - Asia Pacific Region
Color: Gun Metal Gray with Pearl Face Plate
Charge Capability: "AA" (2) or (4)
 "AAA" (2) or (4)
 "AA" (2) and "AAA" (2) Simultaneously

Battery (NiMH)	Capacity (mAh)	Estimated (time)
AA	2650	9.0 hrs
AA	2500	8.5 hrs
AA	2000	7.0 hrs
AAA	1000	10.0 hrs
AAA	900	9.0 hrs
AAA	700	7.0 hrs

Shutoff Mechanism: Delta V Detection
 Timer (10 hours ± 30 minutes)
 Temperature detection at 55°C

Charging Current: AA @ DC 2.8V, 360mA ± 10%
 AAA @ DC 2.8V, 120mA ± 10%

Trickle Charge: None

Input Rating: Universal Voltage: 100-240vac, 50/60Hz

Input Current: Maximum 150mA at AC 120V/60Hz

Input Power: ≤ 6W

Typical Weight: 166.5 grams (5.9 oz.)

Dimensions (mm): 133 x 89 x 32 (H x L x W)

Rev Polarity Protection: Yes

Primary Battery Detection: Yes

Important Notice

This datasheet contains information specific to products manufactured at the time of its publication.

© Energizer

Contents herein do not constitute a warranty.