



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Smart Charger

VERSATILE

- Charges 2 or 4 AA or AAA at a time



SMART

- Charger tells you if the batteries are still rechargeable
- Charger fuel gauge and count-down clock tells you when batteries are done charging.



ECONOMICAL

- Charger maximizes cycle life of the NiMH cells with built in over charge protection
- Energy Star certified for North America and Europe



Before Using Your Charger:
Please read all instructions and cautionary markings on the battery charger, batteries, and device.

Best used with Energizer NiMH batteries.

North American Region

Download Instructions and Warranty Information

[English](#) | [Français](#) | [Español](#)

Product Detail:

Designation: Smart Charger

Color: Black

Charge Capability: "AA" (2) or (4)
"AAA" (2) or (4)

Charging Time: (estimate)	Battery (NiMH)	Capacity (mAh)	Estimated (time)
	AA	2650	8.0 hrs
	AA	2450	7.5 hrs
	AA	2300	7.0 hrs
	AA	2200	6.0 hrs
	AA	1700	5.5 hrs
	AA	1300	4.5 hrs
	AAA	1000	7.0 hrs
	AAA	900	6.5 hrs
	AAA	950	6.5 hrs

Shutoff Mechanism: Delta V Detection
Timer (8 hours)

Charging Current: 2 or 4 x AA, 300mA
2 or 4 x AAA, 120mA

Input Rating: Universal Voltage: 100-240vac, 50/60Hz

Charging indication: Display shows approximate charging time with battery icon and countdown numbers of 8, 6, 4, 2 and 0.

Typical Weight: 116.0 grams (3.9 oz.)

Dimensions (mm): 120 x 70 x 40 (H x L x W)

Volume (cm³): 3146

Plug Type: Folding

Rev Polarity Protection: Yes

Primary Battery Detection: Yes

Important Notice

This datasheet contains information specific to products manufactured at the time of its publication.

© Energizer Holdings, Inc.

Contents herein do not constitute a warranty.

