



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



CONVENIENT

- Charges 2 or 4 NiMH AA's or AAA's



SLEEK

- Sleek Design



EASY

- LED Indicators



Recharge Value Charger



Before Using Your Charger:
Please read all instructions and cautionary markings on the battery charger, batteries, and device.

Best used with Energizer NiMH batteries.

North American Region

[Download User Manual](#)

Product Detail:

Designation: Recharge Value Charger

Model: CHVCM4

Color: Black and White

Charge Capability: "AA" (2) or (4) / "AAA" (2) or (4)
"AA" (2) and "AAA" (2) Simultaneously

Note: Please note battery orientation diagrams in the instructions.



Charging Times: (estimated)	Battery (NiMH)	Capacity (mAh)	Estimated (time)
	AA	1300	5.0 hrs
	AA	2000	8.0 hrs
	AA	2300	10.0 hrs
	AAA	850	7.0 hrs

Shutoff Mechanism: Timer Control ~11 hrs
Delta V Detection

Charging Current: "AA" 260-300mA
"AAA" 120-150mA

Trickle Charge: None

Input Rating: 110-127VAC, 50/60Hz

Typical Weight: 107 grams (3.4 oz.)

Dimensions (mm): 115 x 71 x 62 (H x L x W)

Volume (cm³): 5062

Rev Polarity Protection: Yes

Primary Battery Detection: Yes

Important Notice

This datasheet contains information specific to products manufactured at the time of its publication.

©Energizer Holdings, Inc.

Contents herein do not constitute a warranty.

