imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

1

1

						PANDUIT Part no.	DESCRIPTION WEIGHT				WEIGHT			
						CJ588**Y	8 POSITION, 8 WIRE UNIVERSAL MODULE. TERMINATION CAP IS COLOR CODED FOR EIA/TIA 568A AND/OR 568B WIRING. 1.25 LB/ (566 g/10				1.25 LB/100 PCS (566 g/100 PCS)			
TERMINATION CAP						CJ588A**Y	8 POSIT TERMINA EIA/TIA	SITION, 8 WIRE UNIVERSAL MODULE. INATION CAP IS COLOR CODED FOR TIA 568A WIRING.				1.25 LB/100 PCS (566 g/100 PCS)		
						CJ588B**Y	8 POSIT TERMINA EIA/TIA	ION, 8 FION C 568B	WIRE UNIV AP IS COLO WIRING.	ERSAL R CODE	MODULE. D FOR	1.25 LB/100 PCS (566 g/100 PCS)		
	MOE	DULE					1. 2. 3. ↓ 4. 72 5.	TES: SEE CURRENT CATALOG FOR ADDITIONAL PART NUMBER SUFFIXES TO INDICATE COLOR AND OF PACKAGE QUANTITY. MATERIAL: MODULE HOUSING - ABS - NOMINAL WALL THICKNESS .078(2.0). TERMINATION CAP - POLYCARBONATE ALL MINI-COM MINI-JACK 8 POSITION, 8 WIF MODULES ARE UNIVERSAL IN DESIGN. THEY WILL ACCEPT TWO, THREE, OR FOUR PAI MODULAR PLUGS WITHOUT DAMAGE. THIS PART IS DESIGNED FOR USE WITH MINI-COM OUTLETS. MEETS ALL CATEGORY 50 PERFORMANCE REQUIREMENTS AS DEFINED BY EIA/TIA. DIMENSIONS IN PARENTHESIS ARE IN METRIC.				RE IR		
	[15.9] CJ588**Y, CJ588A**Y, CJ588B**Y TITLE MINI-COM MINI-JACK CATEGORY 5e CONNECTOR MODULE CUSTOMER DRAWING													
					ITEM REVISION NAME									
								DATASET F	ILE NAME M02479MU	_DC334/0	10B	PANDU		
	4/25/14 JSP REFR EJH A. REVISED DRAWING TITLE BLOCK.				02479-334	DIMEN	UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm] .x ± .xxx ± .010 [.3] SEE NOTES							
1 R	4/25/14 3-23-06					02479-334	-XX : .03[.8] ANGLES : THIRD ANGLE PROJECTION DRAWING NUMBER: 02479-334							
REV	DATE	BY	снк	APR	DESCRIPTION	DESCRIPTION			DATE 3-23-06	РR снк WJC	OJECTION Scale NONE	SHT 1 0F 1	4 SIZE A	
								NER						

2

2

В

Α

D10100DA/14