



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## ExStik<sup>®</sup> Waterproof Chlorine Meter

**Direct reading of Total Chlorine down to 0.01ppm**  
Unaffected by color/turbidity of the sample

### Features:

- Direct reading of Total Chlorine provides fast and easy measurements (less than 2 minutes)
- Low detection limit down to 0.01ppm
- Wide dynamic range of measurement up to 10ppm (use dilution method for 10 to 50ppm)
- Unaffected by sample color or turbidity
- Automatic electronic calibration
- Memory stores, tags and recalls up to 15 readings
- Unique flat surface chlorine electrode
- Waterproof to IP67 standard
- The state of the art LCD simultaneously displays ppm of Total Chlorine and Temperature plus analog bargraph indicator
- Complete with meter and flat surface Chlorine electrode, ExTab<sup>®</sup> reagent tablets (50 tests), protective sensor cap, sample cup with cap, four 3V CR-2032 batteries, and 48" (1.2m) neckstrap



Testing Chlorine level in public reservoir

ExTab<sup>™</sup> Chlorine Reagent tablets

3 (20mL) ampules of Chlorine Standard



Patent Pending

### Ordering Information:

<b>CL200</b> .....	ExStik <sup>®</sup> Chlorine Meter
<b>CL203</b> .....	ExTabs <sup>™</sup> Reagent tablets (10pk - 100 tests)
<b>CL204</b> .....	ExTabs <sup>™</sup> Reagent tablets (100pk - 1000 tests)
<b>EX006</b> .....	Weighted base with 5 solution cups
<b>EX007</b> .....	Spare sample solution cups (24pk)
<b>CL205</b> .....	Spare Chlorine electrode
<b>PH105</b> .....	Spare pH electrode
<b>RE305</b> .....	Spare ORP electrode
<b>CL207</b> .....	Chlorine standard (1ppm) –3 ampules (20 mL each)
<b>CA895</b> .....	Carrying Case, Small with Belt Loop
<b>PH115</b> .....	Spare Probe, pH, Refillable Reference
<b>RE305</b> .....	Spare Probe, ORP
<b>EX800</b> .....	ExStik 3-in-1 Kit (Chlorine, pH, Temp)
<b>EX900</b> .....	ExStik 4-in-1 Kit (Chlorine, pH, ORP, Temp)

Specifications	
ppm	0.01 to 10.00ppm (10 to 50ppm using dilution method)
Temperature	23° to 194°F (-5 to 90°C)
Resolution	0.01ppm ; 0.1°F/°C
Accuracy	±10% of reading ±0.01ppm; ±1.8°F/±1°C
Power	four 3V CR-2032 button batteries
Dimensions/Weight	1.4 x 6.8 x 1.6" (35.6 x 172.7 x 40.6mm)/ 3.85oz (110g)

