imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



2000A AC/DC DIGITAL CLAMP METER















2000A AC/DC DIGITAL CLAMP METER

– Non-Contact

The CL900 is an auto-ranging, true root mean square (TRMS) digital clamp meter that measures AC/DC current via the clamp and measures AC/DC voltage, resistance, continuity, frequency, duty-cycle, capacitance, and tests diodes via test-leads. It features a Low Impedance (LoZ) mode for identifying and eliminating ghost or stray voltages, and has a dedicated mode for capturing Inrush Current.

		ALC ALC		Voltage Testing						
				Sensor		MEASUREN	IENT		CL900	l
_						AC/DC Voltage		$\overline{\widetilde{v}}$	1000V	
						AC/DC Current		$\overline{\widetilde{A}}$	2000A	
Extra-Capacity Large Clamp	5		×			Audible Contin	uity	•)))	\checkmark	
						Resistance		Ω	60MΩ	
						True RMS		TRMS	\checkmark	
		/				Non-Contact Te	esting	NCV	\checkmark	
Backlit LCD Display Screen		KLEIN + OZ		Toutured		Low Impedanc	e	LOW Z	\checkmark	
	A REF			Textured Rubberized Clamp Trigger		Inrush Current		<u>N</u> Ã	\checkmark	
	CL900					Backlight 2		`∳ ~	\checkmark	
						Auto-Ranging		AUTO	\checkmark	
	V	V~ OFF	X	- Textured Rubberized Function Selector Switch		Range Hold		RANGE	\checkmark	
	2080					Data Hold		HOLD	\checkmark	
Optional Magnetic Hanger (sold separately) #69417				- Function Buttor	IS	Diode Test		₩	\checkmark	
	2000 A	CIDC Digital Clamp Mi				Capacitance Te	est	-16	\checkmark	
		COC		- LCD Display (with backlight)		Frequency/Dut	y Cycle	Hz %	\checkmark	
		3013				Max/Min Value		MAX/ Min	\checkmark	
		True RMS				Auto Power-Of		APO	1	
		True RMS				LCD Display Co	ount	6000	6000	
	co					DURABILITY				
Integrated	QL					Drop Protection		6.6	ft. (2 m)	
Work light				Test Lead Input Jacks		Safety Rating	\triangle		IV 600V	
										1
		Cat. No.		Pottorico	Longth	14/1-446	Donth	W	eight	ĺ
	KLEIN. TOOLS		UPC 092644+	Batteries	Length	Width	Depth			
		CL900 69235		2 x AAA		imm) 3.9" (99mm) 1.7" (43mm) 17.6 oz (499g) st Leads and 2 AAA Batteries.				
e		THE GLOUD	Includes a		5 Oase, 188	a leaus anu z Al	HA Datter	163.		
			W	ww.klein	tools.	com	1	î\€	€ II	
		T		Vou	~ ~		L			

[O]

Tube

© 2018 Klein Tools, Inc.

Lincolnshire, IL 60069-1418 96533 1/18 B