Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!

Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832
Email & Skype: info@chipsmall.com Web: www.chipsmall.com
Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.





PANDUIT P/N	WEIGHT
CMR19X84	28.00 LB/EACH (12.70 KG/EACH)

NOTES:
1. CAN BE USED WITH ANY INDUSTRY STANDARD 19" COMPONENTS IN ADDITION TO ALL PANDUIT CABLE MANAGEMENT AND PATCH PANEL PRODUCTS.
2. WILL HOLD UP TO 45 SINGLE RACK SPACINGS.
3. EIA SPACING ON RACK: I.E., REF. HOLE SPACING ON UPRIGHT CHANNELS: .625, .625, .500, .625, .625, .500, ETC.
4. ASSEMBLY IS REQUIRED.
5. RACK PART THICKNESSES:
   - UPRIGHT CHANELS: WEB; .14 ±.03
     FLANGE; .19 ±.03
   - TOP BRACKET: .25 ±.03
   - BASE BRACKET: .25 ±.03
6. DIMENSIONS IN PARENTHESIS ARE IN METRIC.
7. ALL ASSEMBLY HARDWARE INCLUDED:
   - (12) 3/8-16 X 1" BLACK HEX HEAD CAP SCREW
   - (12) 3/8" PAINT PIERCING GROUNDING WASHER
   - (1) TUBE OF ANTI-OXIDIZING PASTE
   - (24) 12-24 X .5" SLOTTED PAN HEAD STEEL SCREWS
   - (12) 3/8-16 BLACK HEX NUTS
8. TESTED AND APPROVED 1000 LBS LOAD RATING BY UNDERWRITERS LABORATORIES.
9. RU SPACING NUMBERS ARE CLEARLY PRINTED ON MOUNTING RAILS.





CLOSE UP OF VERTICAL CHANNEL

MODEL FILENAME: M00256AA/08

CAD FILENAME/LAYERS: M00256AA_DC/08A

PANDUIT CORP. TINLEY PARK, ILLINOIS

CABLE MANAGEMENT RACK (CMR19X84) CUSTOMER DRAWING

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:
(.X) ± (.XXX) ±
(.XX) ± ANGLES ±

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.

DRAWN BY: JsP
DATE: 5-29-98
CHK'D: KRKE
MAT'L: ALUMINUM
SCALE: NONE
DRAWING NO.: 00256-05
DWG SIZE: A

REV	DATE	BY	CHK	DESCRIPTION	ECN - R		CUST	SUP	OTH
08A	11-6-08	BAME	DPM	CHANGED NUMBERING ORIENTATION UPDATED HARDWARE NOTE UPDATED REVISION BLOCK	00256-05				
7	10-03-06	LEE	MWH	L. CHANNEL GEOMETRY (HOLES) REVISED K. NOTE 9 WAS 800 LBS LOAD RATING J. NOTE 8 REVISED	00256-05		KRKE	KRKE	
6	11-18-05	TKW	MWH	G. ADDED DIMENSION TO THE BASE BRACKET H. REPOSITIONED DIMENSION TO TE OUTSIDE SURFACE OF VERTICAL CHANNELS	00256-05	ALMY	KRKE	KRKE	
5	11-17-03	RVLE	KRKE	E. REMOVED PEM NUTS F. ADDED (12) 3/8 - 16 BLACK HEX NUTS	00256-05		RTSU	RTSU	
4	1-21-02	JDWE	KRKE	D. CHANGED LOAD RATING FROM 500 LBS.	00256-05		RLFR	RLFR	