



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SPECIFICATION CONTROL DRAWING			0028A0024
CHEMINAX	100 OHM, AWG 28, 7 STRANDS OF AWG 36, TWINAXIAL CABLE	Date	11-25-08
		Revision	A
THIS SPECIFICATION SHEET FORMS A PART OF THE LATEST ISSUE OF RAYCHEM SPECIFICATION 1200.			
CONSTRUCTION DETAILS		ELECTRICAL CHARACTERISTICS	
DIMENSIONS ARE NOMINAL VALUES IN INCHES UNLESS OTHERWISE DESIGNATED.  CONDUCTORS AWG 28, 7 Strands of AWG 36, Silver-Coated High Strength Copper Alloy DIELECTRICS Rayfoam H Colors - White/Light Blue SHIELD AWG 38, Tin-Coated Copper JACKET Modified FEP		CHARACTERISTIC IMPEDANCE 100 ± 7 ohms, Method C at 1 MHz MUTUAL CAPACITANCE 13.4 pF/ft. (nominal) VELOCITY OF PROPAGATION 73% (nominal)	
		ADDITIONAL REQUIREMENTS	
		ELECTRICAL	
		CONDUCTOR RESISTANCE 74.0 ohms/1000 ft. (nominal) INSULATION RESISTANCE 10,000 megohms (minimum) for 1000 ft. JACKET FLAWS SPARK TEST 1.0 kV (rms) IMPULSE TEST 6.0 kV (peak) VOLTAGE WITHSTAND (DIELECTRIC) 1000 volts (rms) (minimum)	
		ENVIRONMENTAL	
		FLAMMABILITY Method B HEAT SHOCK 225°C LOW TEMPERATURE-COLD BEND -55°C/2.75 inch mandrel VOLTAGE WITHSTAND (Post Environmental) 1000 volts (rms), 1 minute	
		PHYSICAL	
		INSULATION (DIELECTRIC) (Prior to Cabling) ELONGATION 50% (minimum) TENSILE STRENGTH 600 lbf/in ² (minimum) JACKET ELONGATION 200% (minimum) TENSILE STRENGTH 2000 lbf/in ² (minimum) JACKET THICKNESS .008 inch (nominal) SHIELD COVERAGE 90% (minimum) BRAID ANGLE 25° (maximum)	
Outer jacket color will be translucent white (designated by a "-9X" appended to the part number, e.g. 0028A0024-9X) unless otherwise specified.		WEIGHT 7.3 lbs/1000 ft. (nominal)	
Designate outer jacket color with a dash number in accordance with MIL-STD-681. Other codes and suffixes may be added to the part number, as necessary, to capture any additional requirements imposed by the purchase order.			
Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.			
The TE logo, Tyco Electronics, Cheminax, Raychem and Rayfoam are trademarks.			



Raychem Wire & Cable
 501 Oakside Avenue
 Redwood City, California 94063-3800
 1-800-227-8816 Fax: 1-650-361-6297

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.