



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



CO220 Desktop Indoor Air Quality CO₂ Monitor



Measures Carbon Dioxide (CO₂), Air Temperature and Humidity, plus calculates Dew Point and Wet Bulb. User settable high/low alarm function is perfect for monitoring air quality and insuring proper air ventilation in conference rooms, schools, greenhouses, factories, hotels, hospitals and anywhere that high levels of carbon dioxide are generated.




Features

- Displays Carbon Dioxide (CO₂) concentrations
- Maintenance free NDIR (non-dispersive infrared) CO₂ sensor
- Carbon Dioxide reading displayed in ppm with six facial icons indicating indoor quality levels (illustrated below)
- Audible CO₂ warning alarm when concentration level exceeds high or low user set point
- Displays Year, Month, Day, and Time
- Min/Max CO₂ value recall function
- Calculates Dew Point and Wet Bulb values
- Calculates statistical weighted averages of TWA (8 hour Time Weighted Average) and STEL (15 minute Short Term Exposure Limit)
- lps% (Liters per second per person) and cfm/p (cubic feet per minute per person)
- Automatic Baseline Calibration function
- Manually store/recall 99 readings
- Complete with AC adaptor

Carbon Dioxide (CO₂) Concentration Levels

Time Weighted Average exposure Limit <8 Hours



Specifications	Range	Resolution
Carbon Dioxide (CO ₂)	0 to 9,999ppm	1ppm
Temperature	14 to 140°F (-10 to 60°C)	0.1°F/°C
Humidity	0.1 to 99.9%RH	0.1%RH
Dew Point	-94 to 140°F (-70 to 60°C)	0.1°F/°C
Wet Bulb	14 to 140°F (-10 to 60°C)	0.1°F/°C
lps%	-1428 to 51 lps%*	1%
cfm/p	-30 to 1 cfm/p*	1 cfm/p
Dimensions	6.1 x 3.4 x 3.2" (155 x 87 x 81mm)	
Weight	5.8oz (165g)	

**Ranges are calculated from 0 to 1000ppm*

Ordering

CO220 Desktop Indoor Air Quality CO₂ Monitor

