



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Magnetic Door Switch Set COM-13247



Description: This is the Magnetic Door Switch Set, a small reed switch assembly specifically designed to alert you when doors, drawers, or any other aperture opens. These types of switches are primarily used in home security systems. One half of the assembly set on a window or door frame and the other attached to the window or door itself. When the switch set is separated from each other the contact is broken and triggers an alarm.

When each magnet piece comes within 20mm of each other they complete the circuit with the internal reed switches. Each Magnetic Door Switch set can accept a max voltage of up to 100V at 500mA. Additionally each set is housed in durable ABS plastic and, with the included screws, can easily mount to most surfaces.

Dimensions: 34 × 41 × 6.5 mm

Includes:

- 1x Magnetic Door Switch Set
- 4x Phillips Mounting Screw

Features:

- Max Voltage: ≤100VDC
- Max Current: ≤500mA
- Max Rating: ≤10W
- Gap: 20±5mm
- Contact Mode: NO