

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







CPH5512

ON

ON Semiconductor®

http://onsemi.com

PIN Diode

Dual parallel PIN Diode for VHF, UHF and AGC 50V, 50mA, r_s =typ 5 Ω , CPH5

Features

- · Composite type with 2 diodes contained in a CPH package currently in use, improving the mounting efficiency greatly
- Small interterminal capacitance (C=0.23pF typ)
- Small forward series resistance ($r_S=5\Omega \text{ typ}$)

Specifications


Absolute Maximum Ratings at Ta=25°C

Parameter	Symbol	Conditions	Ratings	Unit
Reverse Voltage	VR		50	V
Forward Current	I _F		50	Α
Allowable Power Dissipation	Р		350	V
Junction Temperature	Tj		125	°C
Storage Temperature	Tstg		-55 to +125	°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

Package Dimensions

unit : mm (typ) 7017A-001




Product & Package Information

• Package : CPH5

JEITA, JEDEC : SC-74A, SOT-25
Minimum Packing Quantity : 3,000 pcs./reel


Packing Type : TL



Marking



Electrical Connection




Electrical Characteristics at Ta=25°C


Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Reverse Voltage	VR	I _R =10μA	50			V
Reverse Current	IR	V _R =50V			0.1	μΑ
Forward Voltage	VF	I _F =50mA		0.95		V
Interterminal Capacitance	С	V _R =50V, f=1MHz		0.23		pF
SeriesResistance	r _S	IF=10mA, f=100MHz		5		Ω


The specifications shown above are for each individual diode.


Ordering Information

Device	Package	Shipping	memo	
CPH5512-TL-E	PH5512- II -E CPH5		Pb Free	










Embossed Taping Specification

CPH5512-TL-E


1. Packing Format


Package Name	Carrier Tape	Maximum Number of devices contained (pcs)			Packing	format
	Туре	Reel	Inner box	Outer box	Inner $BOX(C-1)$	Outer BOX (A-7)
CPH5	СРН6	3, 000	15, 000	90,000	5 reels contained	6 inner boxes contained
					Dimensions:mm (external)	Dimensions:mm (external)
					183×72×185	440×195×210



7. Taping configuration

2-1. Carrier tape size (unit:mm)






Those with pin 1 index on the feed hole side \cdots TL

Outline Drawing

CPH5512-TL-E

Mass (g) Unit 0.02 *For reference mm 0. 15^{+0. 1}_{-0. 05} 2. 9±0. 1 0.6±0.1 0. 2±0.1 *1 | *1 O. 05±0.05 2. 8±0. 15 1.6±0.1 *1 0.6±0.1 0.95 PIN#1 0.9±0.05 0.05 \$ *1:Lot indication

Land Pattern Example



ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equa