

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







CPI0805F2R2R-10

UNCONTROLLED DOCUMENT


PHYSICAL DIMENSIONS:



B 1.25 [.049] ± 0.20[.008]

C 0.90 [.035] ± 0.10[.004]

D 0.50 [.020] ± 0.20[.008]



ELECTRICAL CHARACTERISTICS:										
	L (μΗ) @ 1MHz ± 20%	DCR ($\frac{\Omega}{2}$) ± 25%	l (Max)							
Nom	2.2	0.25								
Min	1.8	0.1875								
Max	2.6	0.3125	600mA							

NOTES: UNLESS OTHERWISE SPECIFIED


- 1. TAPED AND REELED per CURRENT EIA SPECIFICATIONS 7" REELS, 4000 PCS/REEL, PAPER TAPE.
- 2. TERMINATION FINISH IS 100% MATTE Sn OVER Ni.
- 3. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
- 4. I (MAX.) IS BASED ON THE MAXIMUM SUSTAINED CURRENT APPLIED WHILE MAINTAINING A MAXIMUM TEMPERATURE RISE OF 40°C OVER AMBIENT.
- 5. Operation Temperature TEMP: -55°C~+125°C. (INCLUDING SELF-HEATING)

5 (Hn) 90 (nH) 2 1 1 10 100 1,000

Frequency (MHz)


Ls vs Frequency


LAND PATTERNS FOR REFLOW SOLDERING



(For wave soldering. add 0.763 [0.030] to this dimension)

RECOMMENDED SOLDERING CONDITIONS







DIMENSIONS ARE IN mm [INCHES].				This print is the property of Laird							
				Tech, and is loaned in confidence subject to return upon request and	d		Ind'				
				with the understanding that no		Laird					
				copies shall be made without the written consent of Laird Tech. All							
				rights to design or invention are							
				reserved.	REV						
				PROJECT/PART NUMBER:		PART TYP	E:	DRAWN BY:			
С	CHANGE PLASTIC TAPE TO PAPER TAPE	04/17/14	QU	CPI0805F2R2R-10	C C		FIRE	QU			
В	UPDATE LAIRD LOGO AND NOTES 5	08/05/13	QU	DATE: 03/01/11 SCA	SCALE: NTS		SHEET:				
Α	ORIGINAL DRAFT	03/01/11	QU	, ,							
REV	DESCRIPTION	DATE	INT	CPI0805F2R2R-10-A			1 of 1				