



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



- * LVPECL Output
- * Field Programmable
- * Industry Standard Packaging


- Applications**
- * Serial Communications
 - * Routers
 - * Switches
 - * WAN Interfaces
 - * Test Equipment



Part Numbering Example: CPPE7Z-A7BR-Freq.


CPP	E	7	Z	A7	BR	XX.XXXX
SERIES	OUTPUT	PACKAGE STYLE	ADDED FEATURES	OPERATING TEMP.	STABILITY	FREQUENCY
CPP	E = LVPECL	7 = 5X7 Ceramic	Blank = Bulk T = Tube Z = Tape and Reel	Blank = - 0°C + 70°C A5 = - 20°C + 70°C A7 = - 40°C + 85°C	B6 = ± 100 ppm BP = ± 50 ppm BR = ± 25 ppm	1 ~ 200 MHz

Specifications:	Min	Typ	Max	Unit
Frequency Range:	1		200	MHz
Stability:	-25		+ 25	ppm
Supply Voltage:	3.125	3.3	3.465	V
Operating Temperature:	-40		+ 85	°C
Storage Temperature:	-55		+ 125	°C
Duty Cycle:	45		55	%
Start-Up Time:		3	10	mS
Aging: (ppm/1st Year) Ta=25C, Vdd=3.3V			5	ppm
Static Discharge Voltage:	2000			V
Supply Current:		80	100	mA
Short Circuit Current:		± 50		mA
Jitter (RMS) Period:		6	10	pS
Output Voltage Voh Vol	Vdd - 1.025		Vdd - 1.62	V V
Rise/Fall Time:		0.6	1.5	nS
Output Level:	LVPECL			
Packaging:	Tape and Reel 1000 pcs per Reel			



Tristate internal pull up, output active when high

Dimensions are in mm



- PIN Function
- 1 OE (CMOS)
 - 2 Do Not Connect
 - 3 Ground
 - 4 LVPECL +
 - 5 LVPECL -
 - 6 Vdd

Solder Pad Layout

