



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



STRADA-IP-2X6-T2

IESNA Type II (medium) beam applicable for European P-class standard pedestrian lighting and M-class roads


TECHNICAL SPECIFICATIONS:

Dimensions	71.4 x 173.0 mm
Height	9.2 mm
Fastening	screw
Colour	clear
Box size	476 x 273 x 247 mm
Box weight	8.1 kg
Quantity in Box	120 pcs
ROHS compliant	yes ⓘ











MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour
STRADA-IP-2X6-T2	Lens array	PMMA	clear
2X6-SEAL25	Seal	Silicone	white




PHOTOMETRIC DATA (MEASURED):

<p> bridgelux</p> <p>LED SMD 5050 FWHM Asymmetric Efficiency 94 % Peak intensity 0.660 cd/lm Required components:</p>	
<p> CREE</p> <p>LED XP-G FWHM Asymmetric Efficiency 94 % Peak intensity 1.000 cd/lm Required components:</p>	
<p> CREE</p> <p>LED XP-G2 FWHM Asymmetric Efficiency 94 % Peak intensity 1.000 cd/lm Required components:</p>	
<p> CREE</p> <p>LED XP-G3 FWHM Asymmetric Efficiency 94 % Peak intensity 0.880 cd/lm Required components:</p>	


PHOTOMETRIC DATA (MEASURED):




LED XP-L
FWHM Asymmetric
Efficiency 94 %
Peak intensity 0.770 cd/lm
Required components:




LED XP-L2
FWHM Asymmetric
Efficiency 94 %
Peak intensity 0.700 cd/lm
Required components:



LED XT-E
FWHM Asymmetric
Efficiency 94 %
Peak intensity 1.000 cd/lm
Required components:




LED H35C1 (LEMWA33)
FWHM Asymmetric
Efficiency 94 %
Peak intensity 1.000 cd/lm
Required components:



PHOTOMETRIC DATA (MEASURED):


LUMILEDS

LED LUXEON R
FWHM Asymmetric
Efficiency 94 %
Peak intensity 0.980 cd/lm
Required components:




LUMILEDS

LED LUXEON Rebel ES
FWHM Asymmetric
Efficiency 94 %
Peak intensity 0.970 cd/lm
Required components:




LUMILEDS

LED LUXEON T
FWHM Asymmetric
Efficiency 94 %
Peak intensity 1.000 cd/lm
Required components:



LUMILEDS


LED LUXEON V
FWHM Asymmetric
Efficiency 92 %
Peak intensity 0.770 cd/lm
Required components:



PHOTOMETRIC DATA (MEASURED):


LUMILEDS

LED LUXEON XR-TX (L2T0-xxyy012M)
FWHM Asymmetric
Efficiency 94 %
Peak intensity 1.050 cd/lm
Required components:





LUMILEDS

LED LUXEON Z ES
FWHM Asymmetric
Efficiency 94 %
Peak intensity 1.600 cd/lm
Required components:




NICHIA

LED NVSxx19B/NVSxx19C
FWHM Asymmetric
Efficiency 94 %
Peak intensity 0.980 cd/lm
Required components:



OSRAM Opto Semiconductors


LED Oslon Square PC
FWHM Asymmetric
Efficiency 94 %
Peak intensity 1.000 cd/lm
Required components:



PHOTOMETRIC DATA (MEASURED):


PHILIPS

LED Fortimo FastFlex LED board 2x6 DP G4
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 1.000 cd/lm
 Required components:





SAMSUNG


LED LH351Z
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 1.100 cd/lm
 Required components:








LED SMJQ-D36W12Mx
 FWHM Asymmetric
 Efficiency 93 %
 Peak intensity 0.940 cd/lm
 Required components:



LED SMJQ-D36W12Px
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 0.880 cd/lm
 Required components:




PHOTOMETRIC DATA (MEASURED):

<p>SEOUL SEOUL SEMICONDUCTOR</p> <p>LED Z8Y22 FWHM Asymmetric Efficiency 93 % Peak intensity 0.940 cd/lm Required components:</p>		
<p>SEOUL SEOUL SEMICONDUCTOR</p> <p>LED Z8Y22P FWHM Asymmetric Efficiency 94 % Peak intensity 0.880 cd/lm Required components:</p>		
<p>TOSHIBA Leading Innovation >>></p> <p>LED TL1L4 FWHM Asymmetric Efficiency 93 % Peak intensity 0.970 cd/lm Required components:</p>		
<p>TRIDONIC</p> <p>LED RLE G2 HP 2x6 3000lm FWHM Asymmetric Efficiency 94 % Peak intensity 1.000 cd/lm Required components:</p>		


PHOTOMETRIC DATA (SIMULATED):




LED XHP35 HD
 FWHM Asymmetric
 Efficiency 88 %
 Peak intensity 0.680 cd/lm
 Required components:




LED XHP35 HI
 FWHM Asymmetric
 Efficiency 90 %
 Peak intensity 0.700 cd/lm
 Required components:



LED LUXEON 5050
 FWHM Asymmetric
 Efficiency 90 %
 Peak intensity 0.630 cd/lm
 Required components:



LED LUXEON TX
 FWHM Asymmetric
 Efficiency 88 %
 Peak intensity 0.710 cd/lm
 Required components:




PHOTOMETRIC DATA (SIMULATED):

<p>NICHIA</p> <p>LED NVSW219D FWHM Asymmetric Efficiency 94 % Peak intensity 0.000 cd/lm Required components:</p>	
<p>OSRAM <small>Opto Semiconductors</small></p> <p>LED Duris S8 FWHM Asymmetric Efficiency 91 % Peak intensity 0.740 cd/lm Required components:</p>	
<p>OSRAM <small>Opto Semiconductors</small></p> <p>LED OSCONIQ P 3737 (2W version) FWHM Asymmetric Efficiency 90 % Peak intensity 0.840 cd/lm Required components:</p>	
<p>OSRAM <small>Opto Semiconductors</small></p> <p>LED OSCONIQ P 3737 (3W version) FWHM Asymmetric Efficiency 93 % Peak intensity 0.670 cd/lm Required components:</p>	

PHOTOMETRIC DATA (SIMULATED):


PHILIPS

LED Fortimo FastFlex LED board 2x6 DPX G4
 FWHM Asymmetric
 Efficiency 88 %
 Peak intensity 0.750 cd/lm
 Required components:




SAMSUNG


LED LH351D
 FWHM Asymmetric
 Efficiency 93 %
 Peak intensity 0.620 cd/lm
 Required components:







LED Acrich MJT 4040
 FWHM Asymmetric
 Efficiency 91 %
 Peak intensity 0.890 cd/lm
 Required components:



LED Z5M
 FWHM Asymmetric
 Efficiency 89 %
 Peak intensity cd/lm
 Required components:



PHOTOMETRIC DATA (SIMULATED):

<p> SEOUL SEMICONDUCTOR</p> <p>LED Z5M1/Z5M2 FWHM Asymmetric Efficiency 90 % Peak intensity 0.990 cd/lm Required components:</p>	
<p>TOSHIBA Leading Innovation >>></p> <p>LED TL1L2 FWHM Asymmetric Efficiency 88 % Peak intensity 0.870 cd/lm Required components:</p>	
<p>TOSHIBA Leading Innovation >>></p> <p>LED TL1L3 FWHM Asymmetric Efficiency 86 % Peak intensity 0.570 cd/lm Required components:</p>	

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)