

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China












	<u> </u>	
Product Type	Current Transformer	
Amgis Part Number	CT1200	

SCHEMATIC:





5000Ω

0.45

ELECTRICAL SPECIFICATION:

 $\begin{array}{lll} \text{Rated input current} & = 200 \text{Amps} \\ \text{Primary to Secondary isolation} & = 2500 \text{VAC} \\ \text{Operating Frequency} & = 50 \ / \ 60 \ \text{Hz} \\ \text{Turns Ratio} & = 1 : 1000 \\ \text{DC Resistance} & = 11.00 \ \Omega \\ \end{array}$


Output Voltage = $20.0V @ 200A / 100\Omega, 4.0000W$

Io @ Vrms : 22.20V = $2340 \mu Arms$

Ratio Correction factor (RCF*) = 1.002@10% (Multiply current reading by this factor to compensate for transformer losses)

MECHANICAL SPECIFICAITON:

Pin Side View



All dimensions are in mm Linear dimensional tolerance ±0.2mm

Volt/Amp at rated Ip for different loads

 2000Ω

0.41

500Ω


0.37

100Ω


0.10

Note : Un-Used pin \rightarrow #3

OUTPUT RESPONSE vs INPUT CURRENT @ RATED BURDEN:



TYPICAL EXCITATION CURVE:



SECONDARY RMS EXCITING CURRENT (A)

TRAFO WEIGHT:

Approx. Weight = 0.150 kg / pc

MARKING INFORMATION:



Initial Issue	1	0	K.Shanmugam	01-Dec'2015
Changes	Issue	Rev	Initial	Date