



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Board-to-Cable Connectors

Receptacle: **FI - JP##S - VF10 - R3000**

Cable Plug: **FI - JP##C - R3000**

Plug Shell: **FI - JP##C - SH1 - 9000**
Only orderable in reels

Receptacle: **FI - J##S - VF15N**

Cable Plug: **FI - J##C5 - T3000**

Plug Shell: **FI - J##C2 - SH - D - 10000**
Only orderable in reels

Receptacle: **FI - R_ ## S - HF**

E: EMI shell H: Horizontal
V: Vertical

Cable Plug: **FI - R_ ## H**

E: EMI shell L: Locking Latches
H: Discrete wire crimp
C: Fine-wire coaxial

Cover Shell: **FI - RE ## CL- SH2 - 3000**
Only for coax cable plug

Crimp Contacts: **FI-RC3-1A-1E-15000 (upper)**
FI-RC3-1B-1E-15000 (lower)
Hand Crimp Tool: **CT150-4C-FIR**
Semi-Auto: **3502-FI-2B**

Receptacle: **FI - DP ## SB - VF 20 L 1**

Mated Height
20, 1: 2.0mm
88, Blank: 8.8mm

Cable Plug: **FI - DP ## CL 1**

1: 42 position
Blank: 58 position

Cover Shell: **FI - DP ## CL- SSH - E - 10000**
Only orderable in reels

Single Row

Receptacle: **FI - S_ ##P - HFE**

Cable Plug: **FI - S_ ##S**

E: EMI Shell (Only for 20 pos, FPC) S: Discrete wire crimp
ME: FPC/FFC
MRE: Rev. FPC/FFC

Dual Row

Receptacle: **FI - TWE##PB - VF** Vertical
FI - W_ ##P - HFE Right angle
E: EMI Shell

Cable Plug: **FI - W##S**

Crimp Contacts: **FI-C3-A1-15000**
Hand Crimp Tool: **CT150-4C-FI**
Semi-Auto: **3502-FI-2B**

Receptacle: **FI - X_30S_ _ L - HF**

B: Mid mount R: Reverse
S: Stronger shell

Cable Plug: **FI - X30H**

H: Discrete wire crimp L: Locking latches
C, C2, C2E: Fine-wire coax
MA1, FR: FPC/FFC

Crimp Contacts: **FI-XC3A-1-15000**
Hand Crimp Tool: **CT150-4C-FIX**
Semi-Auto: **3502-FI-2B**

SMT Receptacle: **IL - Z - ##PL - SMTYE**










1: 0.6mm post
Blank: 1.6mm post

Cable Plug: **IL - Z - ##S - S125C3**

Crimp Contacts: **IL- Z-C3-A-15000**
Hand Crimp Tool: **CT150-4C-ILZ**
Semi-Auto: **3502-ILZ-2**

Vertical Recept: **IL - G - ##P - S3T2 - SA**
R/A Recept: **IL - G - ##P - S3L2 - SA**
Cable Plug: **IL - G - ##S - S3C2 - SA**

Crimp Contacts: **IL-G-C2-SC-10000**
Hand Crimp Tool: **CT150-1 -ILG**
Semi-Auto: **3502-ILG-2**
Blank: AWG#28-26
B: AWG#26-24
C: AWG#24-22
D: AWG#20

Series	FI-JP	FI-J	FI-R	FI-DP	FI-X	FI (single row)	FI (dual row)	IL-Z	IL-G
Photo									
Pitch	0.25mm	0.4mm	0.5mm	0.5mm	1.0mm	1.25mm	1.25mm	1.25mm	2.5mm
Discrete Wire AWG	N/A	N/A	#30,32,36	#32-36	#30,32,36	#28,30,32	#28,30,32	#28,30,32	#22,24,26,28
Coax AWG	#44,46	#42,44	#40	#40-42	#32,40	N/A	N/A	N/A	N/A
FPC/FFC	N/A	N/A	FFC (JF04)	N/A	0.14±0.03mm	0.14±0.03mm	N/A	N/A	N/A
Pin Count	40,50	20,25,30,35,40	21,31,41,51	42, 58	30	2-6,8,10,15,20, 25,30	5,7,9,11,13,15,17,19,21,31,41	2-15	2-15
R/A Height	1.1mm	1.58mm	3.8mm	2.0,8.8mm	1.0-2.35mm	1.8mm	3.7mm	3.45mm	6.0mm
Locking	Friction	Friction	Latches	Latches	Latches	Friction	Friction	Friction	Friction
Durability	20 cycles	30 cycles	50 cycles	30 cycles	50 cycles	50 cycles	50 cycles	50 cycles	100 cycles
Current Rating	0.2A	0.3A	0.8A	0.5A	1.0A	1.0A	1.0A	1.0A	3.0A
Voltage Rating	50V	50V	200V	200V	200V	200V	200V	200V	500V
Features	Vertical mating. Small footprint.	Vertical mating. Small footprint.	VESA standard for LCD interface of HD TV. Vertical mount available.	Vertical mating LCD connector compatible with LVDS and eDP.	VESA standard for 1.0mm pitch LVDS interface.	Single row for low profile.	Dual row for smaller footprint.	Multiple terminal lengths available.	Thru-hole. Extremely low cost. Vertical mount available.