



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Circuit Analyzer

Quickly checks for AC outlet load handling capabilities plus Outlet Tester functions
 Large LCD display with color pass/fail test alerts

Features:

- AC Load Tester
 - Selectable loads of 12, 15 and 20 Amps
 - Measures loaded and unloaded AC Line Voltage
 - Calculates and displays % Voltage Drop and Line Impedance
 - Displays Peak Line Voltage and Frequency
- Outlet Tester functions:
 - Neutral to Ground Voltage
 - Hot, Neutral and Ground Impedance
 - GFCI Trip Time
 - GFCI Trip Current
 - Open or Reversed wiring
 - ASCC (Available Short Circuit Current)
- Complete with AC test cord (standard North American 3-prong plug)



Tests 3-wire standard and GFCI receptacles



Display turns red when a problem is detected



NOTE: This product is supplied with a standard North American 3-prong plug

Ordering Information

- CT70Circuit Analyzer
 CT70-ACReplacement AC Power/Tester Cord

Specifications	
AC Voltage	90.0 to 240.0V
Frequency	45.0 to 65.0Hz
Peak Line Voltage	350.0V
% Voltage Drop	0.1 to 99.9%
Dimensions	8 x 2.8 x 2" (203.2 x 71.1 x 50.8mm)
Weight	11.2oz (317.5g)

