



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Specification Sheet

Part Number: CTAM20C2



Cable Tie Anchor Mount, .20" Hole Dia, .20" Max Tie Width, PA66, Black, 100/pkg

|                                |  |
|--------------------------------|--|
| <b>Article Number</b>          | 151-31201  |
| <b>Type</b>                    | CTAM2  |
| <b>Color</b>                   | Black (BK)   |
| <b>Features &amp; Benefits</b> | <ul style="list-style-type: none"><li>•Suitable for applications with minimal space.</li><li>•CTAM has 4-way entry design for use in line or at 90° angle to cable run.</li><li>•CTAM mounts are available in different sizes and materials.</li></ul>   |
| <b>Quantity Per</b>            | bag  |
| <b>Product Description</b>     | Anchor Mounts for cable ties are suitable for applications with minimal space. Anchors are mounted onto the equipment prior to cable installation and take up no more space than the cable itself. Choose between a four-way entry design that can be used either 'in line' or at 90 degrees to the cable run. |
| <b>Short Description</b>       | Cable Tie Anchor Mount, .20" Hole Dia, .20" Max Tie Width, PA66, Black, 100/pkg  |

**Global Part Name**

CTAM2-PA66-BK

**Length L (Imperial)**

0.8

**Length L (Metric)**

20.4

**Fixation Method**

Screw Mounting and Rivet

**Width W (Imperial)**

0.4

**Width W (Metric)**

10.2

**Cable Ties**

T18 - T50

**Height H (Imperial)**

.20

**Height H (Metric)**

5.10

**Cable Tie Width Max (Imperial)**

0.2

**Cable Tie Width Max (Metric)**

5.0

**Mounting Hole Diameter D (Imperial)**

0.2

**Mounting Hole Diameter D (Metric)**

5.2 mm

**Mounting Hole Diameter D Max (Metric)**

5.2

**Material**

Polyamide 6.6 (PA66)

**Material Shortcut**

PA66

**Flammability**

UL 94 V2

**Operating Temperature (Metric)**

-40°F to +185°F (-40°C to +85°C)

**ROHS Complaint**

Yes

**Certification/Specification WEB**

UL

**UL Recognized (US)**

Yes

**UL Recognized (US and Canada)**

Yes

**Package Quantity(Imperial)**

100

**Package Quantity (Metric)**

100

**Customs Number**

3926909987

**Content Unit(BMEcat)**

pcs.