



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# CircuitWorks<sup>®</sup> Water Soluble Flux Pen

## PRODUCT DESCRIPTION

CircuitWorks<sup>®</sup> Water Soluble Flux Pen is designed specifically to apply water soluble flux with precision control. The Water Soluble Flux consists of a neutral pH organic water soluble flux compatible with most solder masks. The high activity organic product cleans easily with water, reducing cleaning cost.

- pH neutral
- Completely portable package
- Cleans with water
- Excellent material compatibility
- Good soldering properties
- ORH1 Classification

## TYPICAL APPLICATIONS

CircuitWorks<sup>®</sup> Flux Dispensing Pens precisely dispense flux on:

- Printed Circuit Boards
- Chip Carriers
- Heat Sinks
- Surface Mount Device Pads
- Switches
- Sockets

## TYPICAL PRODUCT DATA AND PHYSICAL PROPERTIES

### Water Soluble Flux Pen – CW8300

Flux Type	Water Soluble ORH1
Flash Point (TCC)	60°F (16°C)
pH	6.0 – 7.0
Appearance	Yellow Liquid
Odor	Slight

**Shelf life** 2 years

**RoHS Compliant**

## RELIABILITY PROPERTIES

**Copper Mirror Corrosion: High**

Tested to J-STD-004, IPC TM-650, Method 2.3.32

**Corrosion Test: High**

Tested to J-STD-004, IPC-TM-650, Method 2.6.15

**Silver Chromate: Fail**

Tested to J-STD-004, IPC-TM-650, Method 2.3.33

**Chloride and Bromides: 2.2%**

Tested to J-STD-004, IPC-TM-650, Method 2.3.35

**Fluorides by Spot Test: Pass**

Tested to J-STD-004, IPC-TM-650, Method 2.3.35.1

**SIR, IPC (typical): Pass**

Tested to J-STD-004, IPC-TM-650, Method 2.6.3.3

## COMPATIBILITY

CircuitWorks® Water Soluble Flux Pen is generally compatible with most materials used in the electronics industry. As with any cleaning agent, material compatibility should be determined on a non-critical area prior to use.

## USAGE INSTRUCTIONS

For industrial use only.

Read MSDS carefully prior to use.

**Flux Application:** Water Soluble Flux should only be applied to areas to be soldered. Hold pen vertically, touch surface of PCB and briefly depress tip to start liquid flow. Lightly wipe pen tip over surface to be fluxed. Use a ControlWipe™ dry wipe to remove flux buildup.

**Cleaning:** Flux residues must be removed after soldering as they are conductive and corrosive. No neutralizer, saponifiers or detergent are necessary for complete removal of flux residues. It is not recommended to use high mineral content tap water, therefore deionized or softened water may be used for cleaning. The optimum water temperature is 54-66°C (130-150°F). Chemtronics Flux-Off® Water Soluble may also be used as a flux remover.

## TECHNICAL & APPLICATION ASSISTANCE

Chemtronics provides a technical hotline to answer your technical and application related questions. The toll free number is: **1-800-TECH-401.**

## AVAILABILITY

CW8300

9 gm (0.32 oz) Flux Pen

### ENVIRONMENTAL IMPACT DATA

ODP	None	VOC	Yes
HCFC	None	HFC	None

Ozone depletion potential (ODP) is determined in accordance with the Montreal Protocol and U.S. Clean Air Act of 1990. Hydrochlorofluorocarbons (HCFCs) are regulated under the Montreal Protocol as Class II ozone depleting substances. Volatile Organic Compound (VOC) information is calculated on a weight basis using the VOC definition of California Air Resources Board (CARB) Consumer Product Regulations, South Coast Air Quality Management District (SCAQMD) Rule 102 and the Federal definition published in 40 CFR 51.100(s). Hydrofluorocarbons (HFCs) are not currently regulated.

**NOTE:** This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly.

CHEMTRONICS does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

## CHEMTRONICS

8125 COBB CENTER DRIVE

KENNESAW, GA 30152

1-770-424-4888

Rev. B (08/13)

Chemtronics®, Flux-Off® and CircuitWorks® are registered trademarks of Chemtronics. All rights reserved. ControlWipe™ is a trademark of Chemtronics. All rights reserved.

### DISTRIBUTED BY:

--