

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







# RF TRANSFORMER For Wideband RF Applications





- For single-ended to balanced applications
- Value-oriented construction
- Small surface mount package
- Excellent insertion loss
- Various impedance ratios available


Electrical Specifications @ 25°C — Operating Temperature -40°C to +85°C					
Part Number	Impedance Ratio <sup>1</sup> Pri:Sec (±2%)	Turns Ratio <sup>1</sup> Pri:Sec (±2%)	Bandwidth <sup>2, 3</sup> (MHz TYP)	Insertion Loss @ Midband (dB)	Schematic
CX2074	1:4CT	1:2CT	1-500	0.6	А
CX2147	1:1CT	1:1CT	5-200	0.3	Α


NOTE: Optional Tape & Reel packaging can be ordered by adding a "T" suffix to the part number (ex: CX2074T).

### Mechanical

### **Schematic**

# CX2074/CX2147





 Weight
 .0.15 grams

 Tape & Reel
 .1000 /reel

 Tray
 .170 /tray

 Dimensions:
 Inches mm

Unless otherwise specified, all tolerances are  $\pm .010 \over 0.25$ 

# RF TRANSFORMER For Wideband RF Applications



## **Application Notes**


- A. Bandwidth specifications are typical in a 75  $\Omega$  system.
- B. Materials used in the products are UL94-V0 recognized. Products meet requirements of IEC 695-2-2 (Needle Flame Test).
- C. For additional impedance ratios and frequency ranges, please contact Applications Engineering.

#### **Notes from Tables**

- Impedance and turns ratios are specified primary:secondary. (CT=Center Tap).
- 2. Bandwidth is referenced to midband loss.

3. These transformers are verified to operate from -40°C to +85°C. Contact Applications Engineering for performance data.





### **For More Information:**

UNITED KINGDOM **UNITED STATES FRANCE SINGAPORE** TAIWAN, R.O.C. **HONG KONG DISTRIBUTOR** (China/Hong Kong) (Worldwide) (Northern Europe) (Southern Europe) (Southern Asia) (Northern Asia) 12220 World Trade Drive 1 & 2 Huxley Road Zone Industrielle 150 Kampong Ampat 3F-4, No. 81, Sec. 1 9/F, Phase 2, Tai Sang The Surrey Research Park San Diego, CA 92128 #07-01/02 HsinTai Wu Road Shatin Warehouse Centre F-39270 Guildford, Surrey GU2 5RE 6 Wong Chuk Yeung Street U.S.A. Orgelet KA Centre Hsi-Chih, Taipei Hsien http://www.pulseeng.com United Kingdom Taiwan, R.O.C. Fotan, Shatin, Hong Kong France Singapore 368324 TEL: 44 1483 401700 Tel: 886 2 2698 0228 TEL: 858 674 8100 TEL: 33 3 84 35 04 04 TEL: 65 6287 8998 TEL: 852 2788 6588 FAX: 44 1483 401701 FAX: 858 674 8262 FAX: 33 3 84 25 46 41 FAX: 65 6280 0080 FAX: 886 2 2698 0948 FAX: 852 2776 1055

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners.