



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





BCM20732I

Status: NRND: Recommended CYW20732I
RoHS PB Free

BCM20732I

Automotive Grade	No
Automotive Qualified	N
Bluetooth Specification	Bluetooth 4.0
CPU Core	ARM Cortex M3
Cypress Module Area (mm)	6.5 x 6.5 x 1.2
Dedicated ADC (Max. Resolution @ Sampling Rate)	10-bit @ 187 KHz (Static) 13-bit @ 5.8 KHz (Audio)
Device Type	Module
Interfaces	2 UART, 2 SPI, I2C
Max. Operating Frequency (MHz)	24
Max. Operating Temp. (°C)	85
Max. Operating Voltage (V)	3.60
Min. Operating Temp. (°C)	-30
Min. Operating Voltage (V)	1.40
Module Features	Integrated antenna and 24 MHz crystal, FCC and CE compliant
No. of Dedicated Timer/Counter/PWM Blocks	4
No. of GPIOs	14
Partner Modules Available	N
Power-Class	Class 2, Class 3
Product Family	BCM20732
RAM (KB)	60
Silicon Features	Infrared TX/RX

Software Support	Partner SDK
Tape & Reel	N
Wireless Technology	Bluetooth Low Energy

Packaging/Ordering

No. of Pins 48
Package Carrier TRAY
Standard Pack Quantity 1820
Minimum Order Quantity (MOQ) 260
Order Increment 260
HTS Code 8542.31.0000
ECCN None
ECCN Suball 5A992C

Quality and RoHS

Moisture Sensitivity Level (MSL) 3
Peak Reflow Temp. (°C) 260
RoHS Compliant Y
PB Free Y
Lead/Ball Finish Ni/Au